

# TECHNICAL REPORT

ISO/TR  
10465-3

Second edition  
2007-09-01

---

## **Underground installation of flexible glass-reinforced pipes based on unsaturated polyester resin (GRP-UP) —**

### **Part 3: Installation parameters and application limits**

*Installation enterrée de canalisations flexibles renforcées de fibres  
de verre à base de résine polyester insaturée (GRP-UP) —*

*Partie 3: Paramètres d'installation et limites d'application*



Reference number  
ISO/TR 10465-3:2007(E)

© ISO 2007

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-citation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2007

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

## Contents

Page

<b>Foreword</b>	iv
<b>Introduction</b>	v
<b>1 Scope</b>	1
<b>2 Normative references</b>	1
<b>3 Symbols and abbreviated terms</b>	1
<b>4 Parameters for deflection calculations when using an ATV-A 127 type design system</b>	10
<b>4.1 Initial deflection</b>	10
<b>4.2 Long-term deflection calculated using an ATV-A 127 type design system</b>	16
<b>5 Soil parameters, strain coefficients and shape factors for flexural strain calculations</b>	17
<b>5.1 For equations used in ATV-A 127 type design systems</b>	17
<b>5.2 Shape factor, <math>D_f</math></b>	19
<b>6 Influence of soil moduli and pipe stiffness on pipe buckling calculations using ATV-A 127 type design systems</b>	22
<b>6.1 Elastic buckling under internal negative pressure for depths of cover over 1 m</b>	22
<b>6.2 Long-term buckling under sustained external load</b>	23
<b>6.3 Value for <math>S_0</math></b>	23
<b>7 Parameters for rerounding and combined loading calculations</b>	23
<b>7.1 Rerounding</b>	23
<b>7.2 Combined effects of internal pressure and external bending loads</b>	23
<b>8 Traffic loads</b>	24
<b>8.1 General</b>	24
<b>8.2 Influence on allowable initial deflection</b>	24
<b>8.3 Soil pressure from traffic loads</b>	24
<b>9 Influence of sheeting</b>	24
<b>10 Safety factors for gravity pipes and pressure pipes</b>	25
<b>10.1 Gravity pipes</b>	25
<b>10.2 Pressure pipes</b>	27
<b>10.3 Safety factors in buckling calculations</b>	29
<b>Annex A (informative) Soil parameters</b>	30
<b>Annex B (informative) Determination of concentration factors used in ATV-A 127</b>	42
<b>Annex C (informative) Loading coefficients used in ATV-A 127</b>	43
<b>Annex D (informative) Horizontal bedding correction factors</b>	44
<b>Annex E (informative) Selection of long-term stiffness</b>	46
<b>Annex F (informative) Partly residual soil friction used in ATV-A 127 type calculation systems</b>	48
<b>Annex G (informative) Application limits for GRP pressure pipes installed underground</b>	50
<b>Bibliography</b>	63