

Method for evaluation of vulcanization characteristics of styrene-butadiene rubber (SBR, YSBR) (emulsion and solution-polymerized types)

ICS 83.060

Committees responsible for this British Standard

The preparation of this British Standard was entrusted to Technical Committee PRI/50, Natural and synthetic rubbers, upon which the following bodies were represented:

British Rubber Manufacturers' Association Ltd.
Chemical Industries Association
Tropical Growers' Association

This British Standard, having been prepared under the direction of the Sector Board for Materials and Chemicals, was published under the authority of the Standards Board and comes into effect on 15 March 1997

© BSI 1997

First published August 1988
Second edition March 1997

The following BSI references relate to the work on this standard:
Committee reference PRI/50
Draft for comment 91/38416 DC

ISBN 0 580 27169 2

Amendments issued since publication

Amd. No.	Date	Text affected

Contents

	Page
Committees responsible	Inside front cover
National foreword	ii
Specification	
1 Scope	1
2 Normative references	1
3 Sampling and further preparative procedures	2
4 Physical and chemical tests on new rubber	2
5 Preparation of the test mixes	3
6 Evaluation of vulcanization characteristics by a curemeter test	6
7 Evaluation of tensile stress-strain properties of vulcanized test mixes	6
8 Precision	7
9 Test report	9
Annexes	
A (informative) Method B — Internal mixer for initial mixing and mill for final mixing	10
B (informative) Guidance for using precision results	12
C (informative) Comments on precision results	13
Tables	
1 Types of raw styrene-butadiene rubber	1
2 Test formulations	3
3 Alternative test formulations for oil-extended types	4
4 Type 2 precision for stress-strain tests after mixing with a mill mixer	8
5 Type 2 precision after mixing with a miniature internal mixer	9