

INTERNATIONAL STANDARD

ISO 6892

Second edition
1998-03-01

Metallic materials — Tensile testing at ambient temperature

Matériaux métalliques — Essai de traction à température ambiante



Reference number
ISO 6892:1998(E)

Contents	Page
1 Scope	1
2 Normative references	1
3 Principle	1
4 Definitions	2
5 Symbols and designations	4
6 Test piece	4
6.1 Shape and dimensions	4
6.2 Types	7
6.3 Preparation of test pieces	7
7 Determination of original cross-sectional area (S_0)	8
8 Marking the original gauge length (L_0)	8
9 Accuracy of testing apparatus	8
10 Conditions of testing	8
10.1 Speed of testing	8
10.2 Method of gripping	10
11 Determination of percentage elongation after fracture (A)	10
12 Determination of the percentage total elongation at maximum force (A_{gt})	11
13 Determination of proof strength, non proportional extension (R_p)	11
14 Determination of proof strength, total extension (R_t)	12
15 Method of verification of permanent set strength (R_r)	12
16 Determination of percentage reduction of area (Z)	12
17 Accuracy of the results	12
18 Test report	13

© ISO 1998

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
 Case postale 56 • CH-1211 Genève 20 • Switzerland
 Internet central@iso.ch
 X.400 c=ch; a=400net; p=iso; o=isocs; s=central

Printed in Switzerland

Annex A (normative) Types of test piece to be used for thin products: sheets, strips and flats between 0,1 mm and 3 mm thick	20
Annex B (normative) Types of test piece to be used for wire, bars and sections with a diameter or thickness of less than 4 mm	22
Annex C (normative) Types of test piece to be used for sheets and flats of thickness equal to or greater than 3 mm, and wire, bars and sections of diameter or thickness equal to or greater than 4 mm	23
Annex D (normative) Types of test piece to be used for tubes	26
Annex E (informative) Precautions to be taken when measuring the percentage elongation after fracture if the specified value is less than 5 %	28
Annex F (informative) Nomogram for calculating the gauge lengths of test pieces of rectangular cross-section	29
Annex G (informative) Measurement of percentage elongation after fracture based on subdivision of the original gauge length	31
Annex H (informative) Manual method of determination of the percentage total elongation at maximum force for long products such as bars, wire, rods	33
Annex J (informative) An "Error Budget" approach to the estimation of the uncertainty of measurement in tensile testing	34
Annex K (informative) Precision of tensile testing — Results from interlaboratory test programmes	39
Annex L (informative) Bibliography	43