

INTERNATIONAL
STANDARD

ISO
15765-4

Third edition
2016-04-01

**Road vehicles — Diagnostic
communication over Controller Area
Network (DoCAN) —**

**Part 4:
Requirements for emissions-related
systems**

*Véhicules routiers — Diagnostic sur gestionnaire de réseau de
communication (DoCAN) —*

Partie 4: Exigences applicables aux systèmes associés aux émissions

Reference number
ISO 15765-4:2016(E)



© ISO 2016



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

| | Page |
|--|-----------|
| Foreword | v |
| Introduction | vi |
| 1 Scope | 1 |
| 2 Normative references | 1 |
| 3 Terms, definitions, symbols and abbreviated terms | 2 |
| 3.1 Terms and definitions | 2 |
| 3.2 Symbols | 2 |
| 3.3 Abbreviated terms | 2 |
| 4 Conventions | 3 |
| 5 Document overview | 3 |
| 6 External test equipment initialization sequence | 4 |
| 6.1 General | 4 |
| 6.2 Baudrate validation procedure | 7 |
| 6.2.1 BaudrateRecord | 7 |
| 6.2.2 Baudrate validation | 7 |
| 6.2.3 External test equipment error detection provisions | 9 |
| 6.3 CAN identifier validation procedure | 9 |
| 6.3.1 CAN identifier validation procedure OBD | 9 |
| 6.3.2 CAN identifier validation procedure WWH-OBD | 11 |
| 7 Application layer | 13 |
| 8 Session layer | 14 |
| 9 Transport protocol layer | 14 |
| 10 Network layer | 14 |
| 10.1 General | 14 |
| 10.2 Network layer parameters | 14 |
| 10.2.1 Timing parameter values | 14 |
| 10.2.2 Definition of Flow Control parameter values | 15 |
| 10.2.3 Maximum number of legislated OBD/WWH-OBD ECUs | 16 |
| 10.3 Addressing formats | 17 |
| 10.3.1 Normal and fixed addressing format | 17 |
| 10.3.2 Functional addressing | 17 |
| 10.3.3 Physical addressing | 17 |
| 10.4 CAN identifier requirements | 18 |
| 10.4.1 External test equipment | 18 |
| 10.4.2 Legislated OBD/WWH-OBD server/ECU | 18 |
| 10.5 Mapping of diagnostic addresses | 19 |
| 10.5.1 Legislated OBD/WWH-OBD CAN identifiers | 19 |
| 10.5.2 11 bit CAN identifiers | 19 |
| 10.5.3 29 bit CAN identifiers | 20 |
| 10.6 Support of ECUNAME reporting | 21 |
| 11 Data link layer | 21 |
| 12 Physical layer | 21 |
| 12.1 General | 21 |
| 12.2 External test equipment baudrates | 21 |
| 12.3 External test equipment CAN bit timing | 21 |
| 12.3.1 CAN bit timing parameter values | 21 |
| 12.3.2 Nominal baudrate 250 kBit/s | 22 |
| 12.3.3 Nominal baudrate 500 kBit/s | 23 |
| 12.4 External test equipment | 23 |