

---

---

**Non-destructive testing — Ultrasonic  
testing — Characterization and  
verification of ultrasonic thickness  
measuring equipment**

*Essais non destructifs — Contrôle par ultrasons — Caractérisation et  
vérification des appareils de mesure de l'épaisseur par ultrasons*





**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2012

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

Foreword .....	v
Introduction .....	vi
<b>1</b> <b>Scope</b> .....	<b>1</b>
<b>2</b> <b>Normative references</b> .....	<b>1</b>
<b>3</b> <b>Terms and definitions</b> .....	<b>1</b>
<b>4</b> <b>General requirements for compliance</b> .....	<b>1</b>
<b>5</b> <b>Manufacturer's technical specification for ultrasonic thickness measuring equipment</b> .....	<b>2</b>
<b>5.1</b> <b>General</b> .....	<b>2</b>
<b>5.2</b> <b>General attributes</b> .....	<b>2</b>
<b>5.3</b> <b>Display</b> .....	<b>2</b>
<b>5.4</b> <b>Transmitter</b> .....	<b>3</b>
<b>5.5</b> <b>Receiver</b> .....	<b>3</b>
<b>5.6</b> <b>Other information</b> .....	<b>3</b>
<b>6</b> <b>Calibration blocks</b> .....	<b>3</b>
<b>6.1</b> <b>General</b> .....	<b>3</b>
<b>6.2</b> <b>Material</b> .....	<b>3</b>
<b>6.3</b> <b>Shape and size</b> .....	<b>4</b>
<b>7</b> <b>Performance requirements for ultrasonic thickness measuring equipment</b> .....	<b>5</b>
<b>8</b> <b>Probes</b> .....	<b>6</b>
<b>9</b> <b>Group 1 tests</b> .....	<b>7</b>
<b>9.1</b> <b>General</b> .....	<b>7</b>
<b>9.2</b> <b>Equipment required for Group 1 tests</b> .....	<b>7</b>
<b>9.3</b> <b>Stability against temperature</b> .....	<b>7</b>
<b>9.4</b> <b>Low battery warning</b> .....	<b>7</b>
<b>9.5</b> <b>Battery operational time</b> .....	<b>8</b>
<b>9.6</b> <b>Operational voltage range</b> .....	<b>8</b>
<b>9.7</b> <b>Operational current range</b> .....	<b>8</b>
<b>9.8</b> <b>Operational temperature range</b> .....	<b>9</b>
<b>9.9</b> <b>Pulse repetition frequency, PRF</b> .....	<b>9</b>
<b>9.10</b> <b>Transmitter pulse shape, rise-time and peak voltage</b> .....	<b>9</b>
<b>9.11</b> <b>Receiver frequency range of operation</b> .....	<b>11</b>
<b>9.12</b> <b>Minimum and maximum measurable thicknesses</b> .....	<b>11</b>
<b>9.13</b> <b>Accuracy and resolution</b> .....	<b>11</b>
<b>9.14</b> <b>Range of velocity setting (calibration)</b> .....	<b>11</b>
<b>9.15</b> <b>Calibration mechanisms</b> .....	<b>11</b>
<b>9.16</b> <b>Calibration setting storage</b> .....	<b>12</b>
<b>9.17</b> <b>Data storage</b> .....	<b>12</b>
<b>9.18</b> <b>Printing</b> .....	<b>12</b>
<b>9.19</b> <b>Display and recall</b> .....	<b>13</b>
<b>9.20</b> <b>Display response time</b> .....	<b>13</b>
<b>10</b> <b>Group 2 tests</b> .....	<b>13</b>
<b>10.1</b> <b>General</b> .....	<b>13</b>
<b>10.2</b> <b>Equipment required for Group 2 tests</b> .....	<b>13</b>
<b>10.3</b> <b>General characteristics</b> .....	<b>14</b>
<b>10.4</b> <b>General mechanical state and external aspects</b> .....	<b>14</b>
<b>11</b> <b>Group 3 tests</b> .....	<b>14</b>
<b>11.1</b> <b>General</b> .....	<b>14</b>
<b>11.2</b> <b>General mechanical state and external aspects</b> .....	<b>14</b>
<b>11.3</b> <b>Calibration mechanisms</b> .....	<b>14</b>