

Issued 1982-12
Reaffirmed 1993-05
Revised 2011-06

Superseding AS8034A

(R) Minimum Performance Standard for
Airborne Multipurpose Electronic Displays

RATIONALE

The original AS8034 document specified minimum performance standards for Electronic Displays which, at the time of publication, included only Cathode Ray Tube (CRT) displays. The AS8034A revision updated the minimum performance standards to include specific performance standards for Liquid Crystal Displays (LCD) not covered in the originally published document. The current revision, AS8034B, contains clarification on the scope of applicable types of electronic displays, updated references as well as specific updates to the general minimum performance standards for electronic displays identified in Section 3, specific performance standards for LCDs in Section 4.5, and some clarification to CRT specific minimum performance standards in Section 4.4. This document was developed by the SAE A-4 Electronic Display committee and supersedes AS8034 and AS8034A.

TABLE OF CONTENTS

| | | |
|-------|--|---|
| 1. | SCOPE..... | 5 |
| 2. | REFERENCES..... | 6 |
| 2.1 | Applicable Documents | 6 |
| 2.1.1 | SAE Publications..... | 6 |
| 2.1.2 | CIE (Commissions Internationales de l'Eclairage) Publications..... | 6 |
| 2.1.3 | Code of Federal Regulations (CFR)..... | 6 |
| 2.1.4 | EIA Publications | 7 |
| 2.1.5 | FAA Publications..... | 7 |
| 2.1.6 | RTCA/EUROCAE Publications | 7 |
| 2.1.7 | VESA Publications | 7 |
| 2.2 | Related Publications | 7 |
| 2.2.1 | SAE Publications..... | 7 |
| 2.2.2 | FAA Publications..... | 7 |
| 2.2.3 | RTCA/EUROCAE Publications | 8 |
| 2.2.4 | U. S. Government Publications..... | 8 |
| 2.3 | Definitions | 8 |
| 3. | GENERAL STANDARDS..... | 8 |
| 3.1 | Material | 8 |
| 3.2 | Workmanship | 8 |
| 3.3 | Compatibility of Components | 8 |
| 3.4 | Interchangeability..... | 8 |
| 3.5 | Accessibility of Controls | 9 |
| 3.6 | Self-Test Capability..... | 9 |

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be reaffirmed, revised, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2011 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
SAE WEB ADDRESS: http://www.sae.org

**SAE values your input. To provide feedback
on this Technical Report, please visit
<http://www.sae.org/technical/standards/AS8034B>**

| | | |
|--------|---|----|
| 3.7 | Effect of Tests | 9 |
| 3.8 | Malfunctions & Failure Indications | 9 |
| 3.8.1 | Malfunction Indication | 9 |
| 3.8.2 | Power Failure Indication | 9 |
| 3.8.3 | Fail Safe Provision | 9 |
| 3.9 | Multiple Mode Indications | 9 |
| 3.10 | Identification | 10 |
| 3.11 | Display | 10 |
| 3.11.1 | Discernibility | 10 |
| 3.11.2 | Critical Information | 10 |
| 3.11.3 | Information Limit Indication | 10 |
| 3.11.4 | Scale Indications | 10 |
| 3.11.5 | Ambiguity | 10 |
| 3.11.6 | Lighting | 10 |
| 3.12 | Resistance to Dust and Moisture | 11 |
| 3.13 | Mechanical Hazard System Protection | 11 |
| 3.14 | Fire Resistance | 11 |
| 3.15 | Supplemental Heating/Cooling | 11 |
| 4. | MINIMUM PERFORMANCE STANDARDS UNDER STANDARD CONDITIONS | 11 |
| 4.1 | Equipment Functions and Mechanical Operation | 11 |
| 4.2 | Viewing Characteristics | 11 |
| 4.2.1 | Viewing Angle | 11 |
| 4.2.2 | Symbol Alignment | 12 |
| 4.2.3 | Positional Accuracy | 12 |
| 4.2.4 | Drift | 12 |
| 4.2.5 | Line Width | 12 |
| 4.2.6 | Jitter | 12 |
| 4.2.7 | Flicker | 12 |
| 4.2.8 | Symbol Quality and Distortion | 12 |
| 4.2.9 | Crosstalk | 13 |
| 4.2.10 | Image Retention | 13 |
| 4.2.11 | Defects | 13 |
| 4.2.12 | Multiple Images | 13 |
| 4.3 | General Photocolorimetric Characteristics | 13 |
| 4.3.1 | Ambient Illumination Characteristics | 13 |
| 4.3.2 | Luminance Characteristics | 14 |
| 4.3.3 | Luminance and Color Discrimination | 14 |
| 4.3.4 | Color | 15 |
| 4.4 | CRT: | 15 |
| 4.4.1 | Luminance Uniformity | 15 |
| 4.4.2 | Convergence | 15 |
| 4.5 | LCD | 16 |
| 4.5.1 | Luminance | 16 |
| 4.5.2 | Minimum Luminance | 16 |
| 4.5.3 | Contrast Ratio (CR) | 17 |
| 4.5.4 | Viewing Envelope(s) Color Tolerance | 18 |
| 4.5.5 | Gray Scale | 18 |
| 4.5.6 | Specular Reflections | 18 |
| 4.5.7 | Inactivated Segments | 18 |
| 4.5.8 | Response Time | 18 |
| 4.6 | Operating Time | 19 |
| 4.6.1 | Start-Up | 19 |
| 4.6.2 | Lag Time | 19 |
| 4.6.3 | Data Update | 19 |

| | | |
|--------|--|----|
| 5. | MINIMUM PERFORMANCE STANDARDS UNDER ENVIRONMENTAL CONDITIONS | 19 |
| 5.1 | Requirements | 20 |
| 5.1.1 | Display Characteristics | 20 |
| 5.1.2 | Luminance | 20 |
| 5.1.3 | Color | 20 |
| 5.1.4 | Color Registration | 20 |
| 5.1.5 | Display Response Time | 20 |
| 5.1.6 | Mechanical Operation | 20 |
| 5.2 | Definition of Terms | 20 |
| 5.3 | Conditions of Tests | 20 |
| 5.4 | Temperature and Altitude Tests (Section 4.0, DO-160G/ED-14G) | 20 |
| 5.4.1 | Low Temperature Test (including Ground Survival Low Temperature Test and Short-Time Operating Low Temperature Test & Operating Low Temperature Test) | 21 |
| 5.4.2 | High-Temperature Test (including Ground Survival High Temperature Test and Short-Time Operating High Temperature Test and Operating High Temperature Test) | 21 |
| 5.4.3 | In-Flight Loss of Cooling Test | 21 |
| 5.4.4 | Altitude, Decompression and Overpressure Tests (When Required) (Section 4.6, DO-160G) | 21 |
| 5.5 | Temperature Variation Test (Section 5.0, DO-160G/ED-14G) | 21 |
| 5.6 | Humidity Test (Section 6.0, DO-160G/ED-14G) | 21 |
| 5.7 | Operational Shocks and Crash Safety Tests (Section 7.0, DO-160G/ED-14G) | 22 |
| 5.8 | Vibration Tests (Section 8.0, DO-160G/ED-14G) | 22 |
| 5.9 | Explosive Atmosphere Test (When Required) (Section 9.0, DO-160G/ED-14G) | 22 |
| 5.10 | Waterproofness Test (When Required) (Section 10.0, DO-160G/ED-14G) | 22 |
| 5.11 | Fluids Susceptibility Test (When Required) (Section 11.0, DO-160G/ED-14G) | 22 |
| 5.12 | Sand and Dust Test (When Required) (Section 12.0, DO-160G/ED-14G) | 22 |
| 5.13 | Fungus Resistance Tests (When Required) (Section 13.0, DO-160G/ED-14G) | 22 |
| 5.14 | Salt Fog Test (When Required) (Section 14.0, DO-160G/ED-14G) | 22 |
| 5.15 | Magnetic Effect Test (Section 15.0, DO-160G/ED-14G) | 22 |
| 5.16 | Power Input Test (Section 16.0, DO-160G/ED-14G) | 22 |
| 5.16.1 | Normal Operating Conditions | 22 |
| 5.16.2 | Abnormal Operating Conditions | 22 |
| 5.17 | Voltage Spike Test (Section 17.0, DO-160G/ED-14G) | 23 |
| 5.17.1 | Category A Test (When Required) | 23 |
| 5.17.2 | Category B Test (When Required) | 23 |
| 5.18 | Audio Frequency Conducted Susceptibility – Power Inputs (Closed Circuit Test) (Section 18.0, DO-160G/ED-14G) | 23 |
| 5.19 | Induced Signal Susceptibility Test (Section 19.0, DO-160G/ED-14G) | 23 |
| 5.20 | Radio Frequency Susceptibility Test (Radiated and Conducted) (Section 20.0, DO-160G/ED-14G) | 23 |
| 5.21 | Emission of Radio Frequency Energy Test (Section 21, DO-160G/ED-14G) | 23 |
| 5.22 | Lightning Induced Transient Susceptibility (Section 22, DO-160G/ED-14G) | 23 |
| 5.23 | Lightning Direct Effects (When Required) (Section 23, DO-160G/ED-14G) | 24 |
| 5.24 | Icing (When Required) (Section 24, DO-160G/ED-14G) | 24 |
| 5.25 | Electrostatic Discharge (ESD) (Section 25, DO-160G/ED-14G) | 24 |
| 5.26 | X-ray Radiation | 24 |
| 5.27 | UV Radiation | 24 |
| 5.28 | Fogging (Hermetically Sealed or Desiccated Display Units Only) | 24 |
| 5.29 | Thermal Shock (When Required) | 24 |
| 5.30 | Dielectric Test | 25 |
| 6. | TEST PROCEDURES | 25 |
| 6.1 | Test Conditions | 25 |
| 6.2 | Ambient Room Conditions | 25 |
| 6.3 | Power Conditions | 25 |