



Designation: D1835 – 22

# Standard Specification for Liquefied Petroleum (LP) Gases<sup>1</sup>

This standard is issued under the fixed designation D1835; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope\*

1.1 This specification covers those products commonly referred to as liquefied petroleum gases, consisting of propane, propene (propylene), butane, and mixtures of these materials. Four basic types of liquefied petroleum gases are provided to cover the common use applications.

1.2 This specification is applicable to products intended for use as domestic, commercial and industrial heating, and engine fuels.

1.3 The values stated in SI units are to be regarded as standard. The values given in parentheses after SI units are provided for information only and are not considered standard.

1.3.1 The non-SI unit ‘psig’ is the standard unit for footnote C of **Table 1** because that unit of measurement is widely used in North American industry.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

## 2. Referenced Documents

2.1 *ASTM Standards:*<sup>2</sup>

**D1265 Practice for Sampling Liquefied Petroleum (LP) Gases, Manual Method**

**D1267 Test Method for Gauge Vapor Pressure of Liquefied Petroleum (LP) Gases (LP-Gas Method)**

<sup>1</sup> This specification is under the jurisdiction of ASTM Committee D02 on Petroleum Products, Liquid Fuels, and Lubricants and is the direct responsibility of Subcommittee D02.H0 on Liquefied Petroleum Gas.

Current edition approved July 1, 2022. Published July 2022. Originally approved in 1961. Last previous edition approved in 2020 as D1835 – 20. DOI: 10.1520/D1835-22.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard’s Document Summary page on the ASTM website.

**D1657 Test Method for Density or Relative Density of Light Hydrocarbons by Pressure Hydrometer**

**D1837 Test Method for Volatility of Liquefied Petroleum (LP) Gases (Withdrawn 2017)<sup>3</sup>**

**D1838 Test Method for Copper Strip Corrosion by Liquefied Petroleum (LP) Gases**

**D2158 Test Method for Residues in Liquefied Petroleum (LP) Gases**

**D2163 Test Method for Determination of Hydrocarbons in Liquefied Petroleum (LP) Gases and Propane/Propene Mixtures by Gas Chromatography**

**D2420 Test Method for Hydrogen Sulfide in Liquefied Petroleum (LP) Gases (Lead Acetate Method)**

**D2598 Practice for Calculation of Certain Physical Properties of Liquefied Petroleum (LP) Gases from Compositional Analysis**

**D2713 Test Method for Dryness of Propane (Valve Freeze Method)**

**D3700 Practice for Obtaining LPG Samples Using a Floating Piston Cylinder**

**D4175 Terminology Relating to Petroleum Products, Liquid Fuels, and Lubricants**

**D5504 Test Method for Determination of Sulfur Compounds in Natural Gas and Gaseous Fuels by Gas Chromatography and Chemiluminescence**

**D5623 Test Method for Sulfur Compounds in Light Petroleum Liquids by Gas Chromatography and Sulfur Selective Detection**

**D6667 Test Method for Determination of Total Volatile Sulfur in Gaseous Hydrocarbons and Liquefied Petroleum Gases by Ultraviolet Fluorescence**

**D6897 Test Method for Vapor Pressure of Liquefied Petroleum Gases (LPG) (Expansion Method)**

**D7756 Test Method for Residues in Liquefied Petroleum (LP) Gases by Gas Chromatography with Liquid, On-Column Injection**

**D7828 Test Method for Determination of Residue Composition in Liquefied Petroleum Gas (LPG) Using Automated Thermal Desorption/Gas Chromatography (ATD/GC) (Withdrawn 2021)<sup>3</sup>**

**D7994 Test Method for Total Fluorine, Chlorine, and Sulfur**

<sup>3</sup> The last approved version of this historical standard is referenced on [www.astm.org](http://www.astm.org).

\*A Summary of Changes section appears at the end of this standard

in Liquid Petroleum Gas (LPG) by Oxidative Pyrohydrolytic Combustion Followed by Ion Chromatography Detection (Combustion Ion Chromatography-CIC)

2.2 GPA Midstream Association Standard.<sup>4</sup>

GPA Standard 2140 Liquefied Petroleum Gas Specifications and Test Methods

### 3. Terminology

#### 3.1 Definitions:

3.1.1 For definitions of terms used in this specification, refer to Terminology **D4175**.

3.1.2 *commercial butane, n*—a hydrocarbon product for use where low volatility is required.

3.1.3 *commercial PB mixtures, n*—mixtures of propane and butane for use where intermediate volatility is required.

3.1.4 *commercial propane, n*—a hydrocarbon product for use where high volatility is required. Commercial propane is suitable for certain low severity internal combustion engine applications.

3.1.5 *liquefied petroleum gas (LP Gas, LPG), n*—a narrow boiling range mixture of hydrocarbons consisting of propane, propylene, butanes and butylenes, individually or in specified combinations, with limited amounts of other hydrocarbons (such as ethane) and may contain naturally occurring, petroleum-derived, non-hydrocarbons.

3.1.5.1 *Discussion*—LPG is typically maintained in a liquid state by containing it within a closed container or storage tank that can withstand the vapor pressure of the LPG at ambient temperature, or at a low temperature in refrigerated storage.

3.1.5.2 *Discussion*—In many jurisdictions, LPG for fuel purposes is required to be odorized with a stenching agent such as ethyl mercaptan.

3.1.6 *special-duty propane, n*—a product composed chiefly of propane which exhibits superior antiknock characteristics and was specifically developed for use as fuel in spark-ignition internal combustion engines.

### 4. Sampling

4.1 Proper sampling of liquefied gases is extremely important if the test results are to be significant. Obtain representative samples in accordance with Practice **D1265** or Practice **D3700**. In the event of a dispute involving sample integrity when sampling for testing against D1835 requirements, Practice **D3700** shall be used as the referee sampling procedure.

### 5. Detailed Requirements

5.1 The four types of liquefied petroleum gases shall conform to the requirements prescribed in **Table 1**.

### 6. Keywords

6.1 butane; HD-5 propane; liquefied petroleum (LP) gases specifications; LPG; propane; special duty propane

---

<sup>4</sup> Available from GPA Midstream Association, 6060 American Plaza, Suite 700, Tulsa, OK 74135, <http://www.gpaglobal.org>.