This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.



Designation: D2190 - 07 (Reapproved 2021)

# Standard Specification for Vinyl Acetate<sup>1</sup>

This standard is issued under the fixed designation D2190; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\varepsilon$ ) indicates an editorial change since the last revision or reapproval.

# 1. Scope

1.1 This specification covers vinyl acetate.

1.2 The following applies to all specified limits in this standard; for purposes of determining conformance with this standard, an observed value or a calculated value shall be rounded off "to the nearest unit" in the last right-hand digit used in expressing the specification limit, in accordance with the rounding-off method of Practice E29.

1.3 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

1.4 For specific hazard information and guidance, see the supplier's Material Safety Data Sheet for materials listed in this specification.

1.5 This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.

# 2. Referenced Documents

2.1 ASTM Standards:<sup>2</sup>

- D268 Guide for Sampling and Testing Volatile Solvents and Chemical Intermediates for Use in Paint and Related Coatings and Material (Withdrawn 2021)<sup>3</sup>
- D1078 Test Method for Distillation Range of Volatile Organic Liquids
- D1209 Test Method for Color of Clear Liquids (Platinum-Cobalt Scale)
- D1364 Test Method for Water in Volatile Solvents (Karl

Fischer Reagent Titration Method) (Withdrawn 2021)<sup>3</sup>

- D2086 Test Method for Acidity in Vinyl Acetate and Acetaldehyde (Withdrawn 2021)<sup>3</sup>
- D2191 Test Method for Acetaldehyde Content of Vinyl Acetate (Withdrawn 2021)<sup>3</sup>
- D2193 Test Method for Hydroquinone in Vinyl Acetate (Withdrawn 2021)<sup>3</sup>
- D4052 Test Method for Density, Relative Density, and API Gravity of Liquids by Digital Density Meter
- D5386 Test Method for Color of Liquids Using Tristimulus Colorimetry
- E29 Practice for Using Significant Digits in Test Data to Determine Conformance with Specifications
- E300 Practice for Sampling Industrial Chemicals
- 2.2 U.S. Federal Standard:
- PPP-C-2020 Chemicals, Liquid, Dry, and Paste: Packaging of <sup>4</sup>

### 3. Sampling

3.1 Sample the material in accordance with Practice E300.

#### 4. Properties

4.1 The vinyl acetate shall conform to the following requirements:

Distillation range, °C	71.8 to 73.0
Apparent specific gravity, 20/20 °C	0.9335 to 0.9345
Color (HQ grade only), Pt-Co scale, max (Note 1)	5
Water content, weight %, max	0.05
Acetaldehyde content, weight %, max	0.02
Acidity, as acetic acid, weight %, max	0.005
Inhibitor content (HQ)	Α

<sup>A</sup> As agreed upon between the purchaser and the manufacturer.

Note 1—Instrumental Pt-Co color determined by Test Method D5386 has been shown to have no statistically significant difference from Pt-Co color determined by Test Method D1209. However, it is not known whether vinyl acetate was part of the sample set included in the interlaboratory study.

#### 5. Test Methods

5.1 The properties enumerated in this specification shall be determined in accordance with the following ASTM methods:

<sup>&</sup>lt;sup>1</sup> This specification is under the jurisdiction of ASTM Committee D01 on Paint and Related Coatings, Materials, and Applications and is the direct responsibility of Subcommittee D01.35 on Solvents, Plasticizers, and Chemical Intermediates.

Current edition approved July 1, 2021. Published August 2021. Originally approved in 1963. Last previous edition approved in 2013 as D2190 – 07 (2013). DOI: 10.1520/D2190-07R21.

<sup>&</sup>lt;sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

 $<sup>^{3}\,\</sup>text{The}$  last approved version of this historical standard is referenced on www.astm.org.

<sup>&</sup>lt;sup>4</sup> Available from Standardization Documents Order Desk, DODSSP, Bldg. 4, Section D, 700 Robbins Ave., Philadelphia, PA 19111-5098, http://www.dodssp.daps.mil.