
**Indexable hardmetal (carbide) inserts
with wiper edges, without fixing
hole — Dimensions**

*Plaquettes amovibles en métaux-durs (carbures métalliques) avec
arêtes de planage, sans trou de fixation — Dimensions*



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
1 Scope	1
2 Normative references	1
3 Types of inserts	1
4 Interchangeability	2
4.1 Tolerances	2
4.2 Dimensions <i>m</i>	2
5 Designation and marking	2
5.1 Designation	2
5.2 Marking	2
6 Measurement	2
7 Recommended dimensions	3
7.1 Triangular inserts	3
7.1.1 Symmetrical triangular inserts with 90° cutting edge angle, 11° normal clearance, and 11° wiper edge normal clearance	3
7.1.2 Asymmetrical triangular inserts with chamfered corners, 90° cutting edge angle, 11° normal clearance, and 15° wiper edge normal clearance	4
7.1.3 Asymmetrical triangular inserts with chamfered corners, 90° cutting edge angle, 20° normal clearance, and 20° wiper edge normal clearance	5
7.2 Square inserts	6
7.2.1 Symmetrical square inserts with chamfered corner, 75° cutting edge angle, 0° normal clearance, and 0° wiper edge normal clearance	6
7.2.2 Asymmetrical square inserts with chamfered corner, 75° cutting edge angle, 11° normal clearance, and 15° wiper edge normal clearance	7
7.2.3 Symmetrical square inserts with 45° cutting edge angle, 0° normal clearance, and 0° wiper edge normal clearance	8
7.2.4 Asymmetrical square inserts without chamfered corner, 75° cutting edge angle, 20° normal clearance, and 20° wiper edge normal clearance	9
Annex A (normative) Tolerances for <i>d</i>, <i>m</i>, and <i>s</i>	10
Annex B (normative) Method of measurement of “<i>m</i>” dimension	11
Annex C (normative) Range of sizes for inserts with wiper edges, without fixation hole	12
Annex D (informative) Relationship between designations in this International Standard and ISO 13399	14
Bibliography	15