## INTERNATIONAL STANDARD

ISO 5211

Second edition 2017-03

## Industrial valves — Part-turn actuator attachments

Robinetterie industrielle — Raccordement des actionneurs à fraction de tour





## **COPYRIGHT PROTECTED DOCUMENT**

## © ISO 2017, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Contents		Page
Fore	reword	iv
Intr	troduction	v
1	Scope	1
2	Normative references	2
3	Terms and definitions	2
4	Maximum flange torques	3
5	Flange dimensions	
6	Designation	6
7	Dimensions and torques 7.1 General 7.2 Drive by key(s) 7.3 Drive by parallel or diagonal square head 7.4 Drive by flat head 7.5 Drive by improved flat head 7.6 Drive by involute spline 7.7 Drive by bi-square	
8	Position of driven components at interface below part-tu 8.1 Drive by key(s) 8.2 Drive by parallel or diagonal square head or bi-square 8.3 Drive by flat head	e17
9	Dowel pins	20
Ann	nex A (informative) Explanation of calculation	22
Bibl	bliography	24