
**Internal combustion engines —
Piston rings —**

**Part 2:
Half keystone rings made of cast iron**

Moteurs à combustion interne — Segments de piston —

Partie 2: Segments demi-trapézoïdaux fabriqués en fonte moulée



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Overview	1
4 Ring types and designation examples	1
4.1 Type HK — Straight faced half keystone ring 7°	1
4.1.1 General features	1
4.1.2 Designation	2
4.2 Type HKB — Barrel faced half keystone ring 7°	2
4.2.1 General features	2
4.2.2 Designation	4
4.3 Type HKBA — Asymmetrical barrel faced half keystone ring 7° ($h_1 \geq 1,2$ mm)	4
4.3.1 General features	4
4.3.2 Designation	5
5 Common features	5
5.1 Type HK, HKB and HKBA — Half keystone ring	5
5.1.1 Uncoated rings	5
5.1.2 Chromium plated or spray coated rings	6
5.2 Chamfered edges — Type HK, HKB and HKBA rings — Outside and/or inside chamfered edges (KA, KI)	7
5.3 Type HK, HKB and HKBA rings (fully faced, semi-inlaid) — Plating/coating thickness	7
6 Force factors	8
7 Dimensions and forces	8
Annex A (normative) Calculation of measurement width h_3 of half keystone rings	17
Bibliography	18