INTERNATIONAL STANDARD

ISO 6624-4

Second edition 2016-02-15

Internal combustion engines — Piston rings —

Part 4: Half keystone rings made of steel

Moteurs à combustion interne — Segments de piston — Partie 4: Segments semi-trapézoïdaux en acier



ISO 6624-4:2016(E)



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office Ch. de Blandonnet 8 • CP 401 CH-1214 Vernier, Geneva, Switzerland Tel. +41 22 749 01 11 Fax +41 22 749 09 47 copyright@iso.org www.iso.org

Contents Foreword			Page	
			iv	
Introduction		v		
1	Scop	e	1	
2	•	native references		
3	Over	view	1	
4	Ring types and designation examples			
	4.1	Type HK — Straight faced half keystone ring 7°		
		4.1.1 General features		
		4.1.2 Designation	2	
	4.2	Type HKB — Barrel faced half keystone ring 7°	2	
		4.2.1 General features		
	4.0	4.2.2 Designation	4	
	4.3	Type HKBA — Asymmetrical Barrel faced half keystone ring 7° (not recommended		
		for nitrided rings of code NT)		
		4.3.1 General features		
		4.3.2 Designation	0	
5	Common features			
	5.1	Type HK, HKB and HKBA — Half keystone rings	6	
		5.1.1 Nitrided rings (not recommended for HKBA rings with Nitrided code NT)		
		5.1.2 PVD rings		
		5.1.3 Chromium plated or spray coated rings		
	5.2	Type HK, HKB and HKBA rings — Outside and inside rounded edges	7	
	5.3	Type HK, HKB and HKBA rings (fully faced and inlaid) — Plating/coating thickness	8	
	5.4	Type HK, HKB and HKBA rings — Nitrided case depth	9	
6	Force	Force factors		
7	Dime	Dimensions and forces		
Ann	ex A (no	ormative) Calculation of measurement width h ₃ of half keystone rings	19	
Bibliography			20	