



## Road vehicles — Dimensions of two-wheeled mopeds and motorcycles — Terms and definitions

*Véhicules routiers — Dimensions des cyclomoteurs et des motocycles à deux roues — Dénominations et définitions*

First edition — 1981-07-01

## Foreword

ISO (the International Organization for Standardization) is a worldwide federation of national standards institutes (ISO member bodies). The work of developing International Standards is carried out through ISO technical committees. Every member body interested in a subject for which a technical committee has been set up has the right to be represented on that committee. International organizations, governmental and non-governmental, in liaison with ISO, also take part in the work.

Draft International Standards adopted by the technical committees are circulated to the member bodies for approval before their acceptance as International Standards by the ISO Council.

International Standard ISO 6725 was developed by Technical Committee ISO/TC 22, *Road vehicles*, and was circulated to the member bodies in June 1979.

It has been approved by the member bodies of the following countries :

Austria	Italy	South Africa, Rep. of
Belgium	Japan	Spain
Brazil	Korea, Dem. P. Rep. of	Switzerland
Chile	Korea, Rep. of	United Kingdom
Czechoslovakia	Libyan Arab Jamahiriya	USA
France	Netherlands	USSR
Germany, F.R.	Poland	
India	Romania	

No member body expressed disapproval of the document.

## Contents

	Page
1 Scope .....	1
2 Field of application .....	1
3 References .....	1
4 Reference planes and general considerations .....	1
5 Longitudinal median plane (plane <i>Y</i> ) .....	1
6 Terms and definitions .....	3
6.1 Length .....	3
6.2 Width .....	3
6.3 Height .....	3
6.4 Wheel base .....	4
6.5 Front overhang .....	4
6.6 Rear overhang .....	4
6.7 Ground clearance .....	5
6.8 Ramp angle .....	5
6.9 Approach angle .....	5
6.10 Departure angle .....	6
6.11 Castor .....	6
6.12 Castor angle .....	6
6.13 Residual vertical wheel clearance .....	7
6.14 Turning circle diameter .....	7
6.15 Turning clearance circle diameters .....	8
6.16 Banking angle .....	8