
**Measurement of fluid flow in closed
conduits — Velocity-area methods of flow
measurement in swirling or asymmetric
flow conditions in circular ducts by
means of current-meters or Pitot static
tubes**

*Mesurage de débit des fluides dans les conduites fermées — Mesurage
de débit dans les conduites circulaires dans le cas d'un écoulement
giratoire ou dissymétrique par exploration du champ des vitesses au
moyen de moulinets ou de tubes de Pitot doubles*



PDF disclaimer

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



COPYRIGHT PROTECTED DOCUMENT

© ISO 2008

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Normative references	1
3 Symbols	2
4 Principle	2
5 Choice of measuring plane	3
6 Devices for improving flow conditions	3
7 Measurement of local velocities	7
8 Determination of mean flow velocity	14
9 Accuracy of flow-rate estimation	14
Annex A (normative) Detection and removal of regular pressure fluctuations	17
Annex B (normative) Damping of manometers	18
Annex C (normative) Calculation of Pitot static tube locations for method B	20
Annex D (normative) Corrections to be applied when a Pitot static tube is used	22
Annex E (normative) Corrections to be applied when a current-meter is used	23
Annex F (normative) Errors due to non-axisymmetrical velocity distribution	26
Bibliography	27