

INTERNATIONAL STANDARD

ISO
10303-105

First edition
1996-12-15

Industrial automation systems and integration — Product data representation and exchange —

Part 105:

Integrated application resource: Kinematics

Systèmes d'automatisation industrielle et intégration — Représentation et échange de données de produits —

Partie 105: Ressource d'application intégrée: Cinématique

This material is reproduced from ISO documents under International Organization for Standardization (ISO) Copyright License number IHS/ICC/1996. Not for resale. No part of these ISO documents may be reproduced in any form, electronic retrieval system or otherwise, except as allowed in the copyright law of the country of use, or with the prior written consent of ISO (Case postale 56, 1211 Geneva 20, Switzerland, Fax +41 22 734 10 79), IHS or the ISO Licenser's members.



Reference number
ISO 10303-105:1996(E)

ISO 10303-105:1996(E)

Contents

	Page
1 Scope	1
2 Normative references	1
3 Definitions	2
3.1 Terms defined in ISO 10303-1	2
3.2 Terms defined in ISO 10303-42	2
3.3 Terms defined in ISO 8855	3
3.4 Other definitions	3
3.4.1 base	3
3.4.2 frame	3
3.4.3 ground	3
3.4.4 joint	3
3.4.5 kinematics	3
3.4.6 kinematic chain	3
3.4.7 link	3
3.4.8 link frame	3
3.4.9 loop	3
3.4.10 mechanism	3
3.4.11 motion	3
3.4.12 pair	3
3.4.13 pair actuation	4
3.4.14 placement	4
3.4.15 transform	4
3.4.16 SU-parameters	4
3.4.17 world coordinate system	4
4 Symbols and abbreviations	4
4.1 Mathematical symbols	4
4.2 Graphic convention for matrix representation	4
4.3 Abbreviations	4
5 Kinematic structure	6

© ISO 1996

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization
Case Postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

5.1	Introduction	7
5.2	Fundamental concepts and assumptions	8
5.2.1	Kinematic model structure	8
5.2.2	Positioning and placement	9
5.2.3	Positive sense of rotations	10
5.2.4	Shape representations	10
5.2.5	Consistent use of units	11
5.3	kinematic_structure-schema type definitions	11
5.3.1	rigid_placement	11
5.3.2	rotational_range_measure	11
5.3.3	translational_range_measure	12
5.3.4	unlimited_range	12
5.3.5	spatial_rotation	12
5.3.6	ypr_enumeration	12
5.3.7	ypr_rotation	13
5.3.8	kinematic_frame_background	14
5.4	kinematic_structure-schema entity definitions	14
5.4.1	rotation_about_direction	14
5.4.2	kinematic_property_definition	14
5.4.3	kinematic_property_representation_relation	15
5.4.4	kinematic_ground_representation	15
5.4.5	mechanism	16
5.4.6	mechanism_base_placement	17
5.4.7	initial_state	18
5.4.8	kinematic_structure	19
5.4.9	kinematic_joint	19
5.4.10	kinematic_link	20
5.4.11	kinematic_link_representation_relation	21
5.4.12	kinematic_link_representation	21
5.4.13	kinematic_link_representation_association	22
5.4.14	kinematic_frame_background_representation	23
5.4.15	kinematic_frame_based_transformation	24
5.4.16	kinematic_frame_background_representation_association	24
5.4.17	su_parameters	25
5.4.18	kinematic_pair	27
5.4.19	pair_actuator	29
5.4.20	pair_value	31
5.4.21	simple_pair_range	31
5.4.22	revolute_pair	31
5.4.23	revolute_pair_value	32
5.4.24	revolute_pair_range	32
5.4.25	prismatic_pair	33
5.4.26	prismatic_pair_value	33
5.4.27	prismatic_pair_range	34
5.4.28	screw_pair	35
5.4.29	screw_pair_value	36