

---

---

**Smoke alarms using scattered light,  
transmitted light or ionization**

*Détecteurs de fumée à lumière dispersée, lumière transmise  
ou ionisation*



Reference number  
ISO 12239:2010(E)

© ISO 2010

**PDF disclaimer**

This PDF file may contain embedded typefaces. In accordance with Adobe's licensing policy, this file may be printed or viewed but shall not be edited unless the typefaces which are embedded are licensed to and installed on the computer performing the editing. In downloading this file, parties accept therein the responsibility of not infringing Adobe's licensing policy. The ISO Central Secretariat accepts no liability in this area.

Adobe is a trademark of Adobe Systems Incorporated.

Details of the software products used to create this PDF file can be found in the General Info relative to the file; the PDF-creation parameters were optimized for printing. Every care has been taken to ensure that the file is suitable for use by ISO member bodies. In the unlikely event that a problem relating to it is found, please inform the Central Secretariat at the address given below.



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2010

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
Case postale 56 • CH-1211 Geneva 20  
Tel. + 41 22 749 01 11  
Fax + 41 22 749 09 47  
E-mail [copyright@iso.org](mailto:copyright@iso.org)  
Web [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

Page

Foreword .....	v
Introduction.....	vi
<b>1 Scope .....</b>	<b>1</b>
<b>2 Normative references .....</b>	<b>1</b>
<b>3 Terms and definitions .....</b>	<b>2</b>
<b>4 General requirements .....</b>	<b>4</b>
4.1 Compliance .....	4
4.2 Alarm condition .....	4
4.3 Mains-on visual indicator .....	5
4.4 Fault condition visual indicator — Optional function.....	5
4.5 Smoke alarm signals.....	5
4.6 Test facility .....	5
4.7 Means of calibration.....	5
4.8 User-replaceable components .....	5
4.9 Primary power source.....	5
4.10 Secondary power source.....	6
4.11 Battery connections .....	6
4.12 User-replaceable battery.....	7
4.13 Electrical safety .....	7
4.14 Connection of external ancillary devices.....	7
4.15 Terminals for external conductors .....	7
4.16 Protection against the ingress of foreign bodies .....	7
4.17 Interconnectable smoke alarms — Optional function .....	8
4.18 Alarm-silence facility — Optional function .....	8
4.19 Radioactive material in type B smoke alarms .....	8
4.20 Smoke alarms with voice — Optional function .....	8
4.21 Marking.....	9
4.22 Data .....	10
4.23 Additional requirements for software controlled smoke alarms.....	11
<b>5 Tests .....</b>	<b>12</b>
5.1 General .....	12
5.2 Directional dependence .....	16
5.3 Initial sensitivity.....	16
5.4 Repeatability .....	16
5.5 Air movement.....	17
5.6 Dazzling .....	17
5.7 Dry heat (operational) .....	18
5.8 Cold (operational).....	19
5.9 Damp heat (operational) .....	20
5.10 Sulfur dioxide (SO <sub>2</sub> ) corrosion .....	21
5.11 Impact (operational) .....	22
5.12 Vibration, sinusoidal (operational) .....	23
5.13 Vibration, sinusoidal (endurance) .....	24
5.14 Extended temperature (operational) — Optional function .....	25
5.15 Electromagnetic compatibility (EMC) immunity tests (operational) .....	25
5.16 Fire sensitivity .....	26
5.17 Battery-low condition.....	27
5.18 85 dBA Sound output — Optional function .....	28
5.19 70 dBA Sound output — Optional function .....	29