
**Mechanical vibration — Rotor
balancing —**

**Part 31:
Susceptibility and sensitivity of
machines to unbalance**

Vibrations mécaniques — Équilibrage des rotors —

Partie 31: Susceptibilité et sensibilité des machines aux balourds



Reference number
ISO 21940-31:2013(E)

© ISO 2013



COPYRIGHT PROTECTED DOCUMENT

© ISO 2013

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Case postale 56 • CH-1211 Geneva 20
Tel. + 41 22 749 01 11
Fax + 41 22 749 09 47
E-mail copyright@iso.org
Web www.iso.org

Published in Switzerland

Contents

	Page
Foreword	iv
Introduction	vi
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Machine susceptibility classification	1
4.1 General	1
4.2 Type I: Low susceptibility	2
4.3 Type II: Moderate susceptibility	2
4.4 Type III: High susceptibility	2
4.5 Machine susceptibility correction factors	2
5 Modal sensitivity	2
5.1 General	2
5.2 Modal sensitivity ranges	3
5.3 Characteristics of modal sensitivity ranges	3
5.4 Values of modal sensitivity	3
5.5 Operating speed	7
5.6 Transient speed	9
6 Experimental determination of modal sensitivity near resonance speed under operational conditions	10
6.1 General	10
6.2 Nyquist diagram procedure	10
6.3 Bode diagram procedure	10
7 Numerical values for the local sensitivity	11
8 Experimental determination of the local sensitivity	12
8.1 General	12
8.2 Procedure	12
9 Damped unbalance sensitivity analysis	13
Annex A (informative) Explanations of terms	14
Annex B (informative) Example of polar plot diagram procedure	16
Annex C (informative) Examples of classification according to modal sensitivity	17
Annex D (informative) Example of mathematical model applied unbalance	18
Bibliography	19