
**Hydraulic fluid power — Method
for evaluating the buckling load of a
hydraulic cylinder**

*Transmissions hydrauliques — Méthode d'évaluation du flambage
d'un vérin*



COPYRIGHT PROTECTED DOCUMENT

© ISO 2016, Published in Switzerland

All rights reserved. Unless otherwise specified, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office
Ch. de Blandonnet 8 • CP 401
CH-1214 Vernier, Geneva, Switzerland
Tel. +41 22 749 01 11
Fax +41 22 749 09 47
copyright@iso.org
www.iso.org

Contents

Page

Foreword	iv
Introduction	v
1 Scope	1
2 Symbols and units	1
2.1 General.....	1
2.2 Additional notations.....	2
3 General principles	3
3.1 Purpose.....	3
3.2 Description.....	3
3.3 Dimensional layout of hydraulic cylinder.....	3
3.4 Common calculation of maximum stress in the rod (for all mounting types) σ_{\max}	5
3.4.1 Deflexion curve.....	6
3.4.2 Bending moment.....	6
3.4.3 Maximum value of the bending moment.....	6
3.4.4 Maximum stress of the piston rod.....	7
3.4.5 Mounting types of the cylinder tube and piston rod.....	7
4 Case of pin-mounted hydraulic cylinders	8
4.1 Model of the hydraulic cylinder and unknown values.....	8
4.2 Linear system.....	9
4.3 Critical buckling load.....	9
4.4 Greatest allowable compressive load.....	10
5 Case of hydraulic cylinders fixed at the beginning of the cylinder tube and pin mounted at the end of the piston rod	10
5.1 Critical buckling load.....	10
5.2 Linear system.....	10
6 Case of hydraulic cylinders pin mounted at the beginning of the cylinder tube and fixed at the end of the piston rod	11
6.1 Critical buckling load.....	11
6.2 Linear system.....	11
7 Case of hydraulic cylinders fixed at both ends	12
7.1 Critical buckling load.....	12
7.2 Linear system.....	12
8 Case of hydraulic cylinders fixed at the beginning of the cylinder tube and free at the end of the piston rod	13
8.1 Critical buckling load.....	13
8.2 Linear system.....	14
9 Case of hydraulic cylinders fixed at both ends with free movement allowed at the end of the piston rod	15
9.1 Critical buckling load.....	15
9.2 Linear system.....	15
Annex A (informative) Example of numerical results	17
Bibliography	19