



SURFACE VEHICLE RECOMMENDED PRACTICE	J1773	JUN2014
	Issued 1995-01 Stabilized 2014-06	
	Superseding J1773 MAY2009	
SAE Electric Vehicle Inductively Coupled Charging		

RATIONALE

Need to vote to stabilize this document for historical reference. This document will no longer be updated. 5-year review/action is due.

STABILIZED NOTICE

This document has been declared "Stabilized" by the SAE Hybrid - EV Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2014 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

SAE values your input. To provide feedback on this Technical Report, please visit http://www.sae.org/technical/standards/J1773_201406

Foreword—This is a Recommended Practice and in no manner should be interpreted as a standard of the SAE. This proposal should not be interpreted as an endorsement of inductive charging by the SAE. This document contains 44 pages, including this page, and should not be used as a design tool if any of the pages are missing. Portions of this document may be revised to keep pace with experience and technological advances.

TABLE OF CONTENTS

1.	Scope	3
1.1	General Inductive Charging System Description.....	3
2.	References	4
2.1	Applicable Publications	4
2.1.1	SAE Publications	4
2.1.2	NFPA Publication	4
2.1.3	Federal Communications Commission (FCC).....	4
2.1.4	Underwriters Laboratories, Inc.	4
2.2	Related Publications.....	4
3.	Definitions.....	5
4.	Inductive Charging Interface Requirements	6
4.1	Power Transfer	6
4.1.1	Average Output Voltage Range	6
4.1.2	Maximum Average Output Current as a Function of Average Output Voltage.....	6
4.1.3	Power Transfer Frequency Range	6
4.1.4	Maximum Allowable Average Output Current versus Frequency.....	6
4.1.5	Maximum Allowable RMS Input Current versus Frequency.....	8
4.1.6	Equivalent Circuit Parameters at Charge Coupling Interface.....	8
4.2	Heat Transfer	9
4.2.1	Excess Inductive Connector Power Dissipation	9
4.2.2	Inductive Connector Touch Temperature.....	9
4.3	Communications.....	9
4.3.1	IR Communications Metrics.....	9
4.4	Physical Compatibility.....	10
4.4.1	Inductive Connector	10
4.4.1.1	Critical Dimensions.....	10

4.4.1.2	Orientation	10
4.4.1.3	Connection Present Magnet Location.....	10
4.4.1.4	Connection Present Magnet Strength.....	10
4.4.1.5	Tactile Feel Indents	10
4.4.1.6	EMI Shield Contact Zone Location	10
4.4.1.7	EMI Shield Contact Zone Impedance	10
4.4.1.8	IR Transceiver Interface Location.....	10
4.4.1.9	Stop Receptacle Locations	12
4.4.2	Inductive Vehicle Inlet.....	12
4.4.2.1	Critical Dimensions	12
4.4.2.2	Alignment.....	12
4.4.2.3	EMI Shield Contact Zone Location	12
4.4.2.4	Grounding of EMI Shield Contact Zone	13
4.4.2.5	IR Transceiver Alignment	13
4.5	Electromagnetic Emissions.....	13
4.5.1	SAE Charging System Requirements.....	13
4.5.2	FCC Charging System Requirements.....	13
5.	Application Requirements	14
5.1	Environment.....	14
5.1.1	Performance Requirements.....	14
5.1.1.1	External Touch Temperature	14
5.1.1.2	Operational and Storage Temperature	14
5.1.1.3	External Contaminants	14
5.1.1.4	Vibration.....	14
5.1.1.5	Pass Criteria	14
5.1.1.6	Material	14
5.1.1.7	Fluid Egress.....	14
5.2	Charger Requirements	14
5.2.1	Power Level Compatibility	14
5.3	Vehicle Requirements.....	14
5.3.1	Power Level Compatibility	14
6	Notes	14
6.1	Marginal Indicia.....	14
Appendix A	Software Interface.....	15
A.1	Scope.....	15
A.2	Software States	15
A.3	Message Structure.....	18
A.4	Message Definitions	20
A.4.1	Vehicle-to-Charger Messages	20
A.4.2	Charger-to-Vehicle Messages	23
A.5	Fault Detection and Handling	25
A.6	Message Summary.....	26
A.7	Glossary.....	26
Appendix B	Level 3 Compatibility.....	27
B.1	Scope.....	27
B.2	Level 3 Power Compatibility System Design	27
B.2.1	Hardware Power Level Comparison Requirements.....	28
B.2.2	Software Power Level Comparison Requirements	28
B.3	Charger Controller Requirements.....	28
B.4	Vehicle Charge Controller Requirements	28