



SURFACE VEHICLE STANDARD

J1926™-1

SEP2016

Issued 1988-08
Revised 2016-09

Superseding J1926-1 FEB2010

Connections for General Use and Fluid Power - Ports and Stud Ends with
ASME B1.1 Threads and O-Ring Sealing - Part 1: Threaded Port with O-Ring Seal
in Truncated Housing

RATIONALE

This specification was revised to clarify where the d5 dimension is measured.

FOREWORD

SAE J1926 consists of the following parts, under the general title:

Connections for general use and fluid power Ports and stud ends with ASME B1.1 threads and O-ring sealing:

- Part 1: Port with O-Ring Seal in Truncated Housing
- Part 2: Heavy-Duty (S Series) Stud Ends
- Part 3: Light-Duty (L Series) Stud Ends
- Part 4: External Hex and Internal Hex Inch Port Plugs - Dimensions, Design, Test Methods and Requirements

These standards define performance requirements, dimensions, and designs for port and stud end connections for heavy-duty in Part 2 and light-duty in Part 3. Significant testing through over 50 years of use has confirmed the performance requirements of these ports and stud ends.

In fluid power systems, power is transmitted and controlled through a fluid (liquid or gas) under pressure within an enclosed circuit. In general applications, a fluid may be conveyed under pressure. Components are connected through their threaded ports by fluid conductor fittings to tubes and pipes, or to hose fittings and hoses.

Ports are an integral part of fluid power components such as pumps, motors, valves, cylinders, etc.

1. SCOPE

This part of SAE J1926 specifies dimensions for fluid power and general use ports with inch threads in accordance with ASME B1.1 for use with adjustable and nonadjustable stud ends shown in SAE J1926-2 and SAE J1926-3.

Ports in accordance with this part of SAE J1926 may be used at working pressures up to 63 MPa for nonadjustable stud ends and up to 40 MPa for adjustable stud ends. The permissible working pressure depends upon materials, design, working conditions, application, etc.

For threaded ports and stud ends specified in new designs for hydraulic fluid power applications, only ISO 6149 shall be used. Threaded ports and stud ends in accordance with ISO 1179, ISO 9974, and ISO 11926 shall not be used for new designs in hydraulic fluid power applications.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2016 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/J1926/1_201609**

2. REFERENCES

2.1 Applicable Documents

The following standards contain provisions which, through reference in this text, constitute provisions of this document. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this document are encouraged to investigate the possibility of applying the most recent edition of the standards indicated as follows. Members of IEC and ISO maintain registers of currently valid International Standards.

2.1.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or +1 724-776-4970 (outside USA), www.sae.org.

SAE 1926-2 Connections for General Use and Fluid Power—Ports and Stud Ends with ASME B1.1 Threads and O-Ring Sealing—Part 2: Heavy Duty (S Series) Stud Ends

SAE 1926-3 Connections for General Use and Fluid Power—Ports and Stud Ends with ASME B1.1 Threads and O-Ring Sealing—Part 3: Light Duty (L Series) Stud Ends

2.1.2 ISO Publications

Copies of these documents are available online at <http://webstore.ansi.org/>

ISO 5598 Fluid power systems and components - Vocabulary

ISO 19879 Metallic tube connections for fluid power and general use - Test methods for hydraulic fluid power connections

2.1.3 ASME Publications

Available from the American Society of Mechanical Engineers, 22 Law Drive, PO Box 2900, Fairfield, NJ 07007-2900, Tel: 973-882-1170, www.asme.org.

ASME B1.1 Unified Inch Screw Threads (UN and UNR Thread Form)

2.2 Related Publications

The following publications are provided for information purposes only and are not a required part of this SAE Technical Report.

2.2.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or +1 724-776-4970 (outside USA), www.sae.org.

SAE J514 Hydraulic Tube Fittings

SAE J1453 Fitting - O-Ring Face Seal