



SURFACE VEHICLE STANDARD

J1926™-3

SEP2016

Issued 1988-08
Revised 2016-09

Superseding J1926-3 MAR2010

Connections for General Use and Fluid Power - Ports and Stud Ends with
ASME B1.1 Threads and O-Ring Sealing - Part 3: Light-Duty (L-Series) Stud Ends

RATIONALE

This document was revised in order to move the optional inch hex sizes and dimensions to Appendix B.

In an effort to standardize within a global market and ensuring that companies can remain competitive in an international market, it is the intent to convert to metric hex sizes which will:

- lead to one global system
- guide users to preferred system
- reduce complexity
- eliminate duplications

The optional inch hexes now contain the note "NOT TO BE USED FOR NEW DESIGN" in accordance with the Metric Hex Resolution approved during the March 2008 FCCTC meeting.

FOREWORD

SAE J1926 consists of the following parts, under the general title:

Connections for general use and fluid power Ports and stud ends with ASME B1.1 threads and O-ring sealing:

- Part 1: Port with O-ring Seal in Truncated Housing
- Part 2: Heavy-Duty (S Series) Stud Ends
- Part 3: Light-Duty (L Series) Stud Ends These standards define performance requirements, dimensions, and designs for port and stud end connections for heavy-duty in Part 2 and light-duty in Part 3. Significant testing through 50 years of use has confirmed the performance requirements of these ports and stud ends. SAE J1926-3 stud ends originated with 37° flare connectors shown in SAE J514.

In fluid power systems, power is transmitted and controlled through a fluid (liquid or gas) under pressure within an enclosed circuit. In general applications, a fluid may be conveyed under pressure. Components are connected through their threaded ports by stud ends on fluid conductor fittings to tubes/pipes, or to hose fittings and hoses.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2016 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/J1926/3_201609**

1. SCOPE

This part of SAE J1926 specifies dimensions, performance requirements, and test procedures for adjustable and nonadjustable light-duty (L series) stud ends with ASME B1.1 threads for use in fluid power and general applications and the O-rings used with them.

Stud ends in accordance with this part of SAE J1926 may be used at working pressures up to 35 MPa for nonadjustable and adjustable stud ends. The permissible working pressure depends upon materials, design, working conditions, application, etc.

For threaded ports and stud end specified in new designs for hydraulic fluid power applications, only ISO 6149 shall be used. Threaded ports and stud ends in accordance with ISO 1179, ISO 9974, and ISO 11926 shall not be used for new design in hydraulic fluid power applications.

Conformance to the dimensional information does not guarantee rated performance. Each manufacturer shall perform testing according to the specification contained in this document to ensure that components made to this document comply with the performance rating.

Appendices A and B of this document are informative.

NOTE: This document specifies inch as well as metric hexes for the stud ends. Therefore, any product drawing specifying stud ends in accordance with this document must specify hex type, inch or metric, to assure getting intended hex.

Stud ends or parts specified before January 1, 2010 using this standard, shall be supplied with inch hexes, unless otherwise specified.

2. REFERENCES

(NOTE: Documents in this section have been rearranged to better classify them as either applicable or related)

2.1 Applicable Documents

The following standards contain provisions which, through reference in this text constitute provisions of this document. At the time of publication, the editions indicated were valid. All standards are subject to revision, and parties to agreements based on this document are encouraged to investigate the possibility of applying the most recent edition of the standards indicated as follows. Members of IEC and ISO maintain registers of currently valid International Standards.

2.1.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or +1 724-776-4970 (outside USA), www.sae.org.

SAE J515	Specification for O-ring Materials Used with Hydraulic Connectors
SAE J1926-1	Connections for General Use and Fluid Power - Ports and Stud Ends with ASME B1.1 Threads and O-ring Sealing - Part 1: Threaded Port with O-ring Seal in Truncated Housing
SAE J2593	Information Report for the Installation of Fluid Conductors and Connectors

2.1.2 ISO Publications

Copies of these documents are available online at <http://webstore.ansi.org/>

ISO 4759 -1 Tolerances for fasteners – General plan and selection for screws, bolts and nuts – Product grades A, B and C

ISO 5598 Fluid power systems and components – Vocabulary

ISO 19879 Metallic tube connections for fluid power and general use – Test methods for hydraulic fluidpower connections

2.1.3 ASME Publications

Available from American Society of Mechanical Engineers, 22 Law Drive, P.O. Box 2900, Fairfield, NJ 07007-2900, Tel: 973-882-1170, www.asme.org.

ASME B1.1 Unified Inch Screw Threads (UN and UNR Thread Form)

2.2 Related Publications

The following publications are provided for information purposes only and are not a required part of this SAE Technical Report.

2.2.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or +1 724-776-4970 (outside USA), www.sae.org.

SAE J514 Hydraulic Tube Fittings

SAE J1926-2 Connections for General Use and Fluid Power—Ports and Stud Ends with ASME B1.1 Threads and O-ring Sealing - Part 2: Heavy-Duty (S Series) Stud Ends

SAE J1926-4 Connector for Fluid Power and General Use—Ports and Stud Ends with ASME B1.1 Threads and O-ring Seal - Part 4: External Hex and Internal Hex Inch Port Plugs—Dimensions, Design, Test Methods and Requirements