



SURFACE VEHICLE INFORMATION REPORT



J2024 MAY2013

Issued 1993-06
Reaffirmed 2013-05

Superseding J2024 SEP2007

Contaminants for Testing Air Brake Components and Auxiliary Pneumatic Devices—Truck and Bus

RATIONALE

No changes or updates required at this time. RP to be Reaffirmed "as is".

1. SCOPE

This SAE Information Report establishes a minimum level of uniform recipes for contaminants which may be used when durability testing pneumatic components to obtain additional information on how a device may perform under more true-to-life operating conditions. This type of contamination testing, however, is not meant to replace the type of performance testing described in SAE J1409 and SAE J1410. Durability testing in the presence of contamination, however, will yield results more reflective of actual in-service field conditions and provide an additional evaluation of pneumatic devices.

While the contaminant supply rate and other test criteria of the device being tested must be set by the device manufacturer or user, the items covered in this document will be:

- 1.1 Formula for contaminated oil to be used as a lubricant when testing air compressors.
- 1.2 Formula for a contaminant to be used when testing pneumatic system components other than air compressors.
- 1.3 Other contaminants.

2. REFERENCES

2.1 Applicable Publications

The following publications form a part of this specification to the extent specified herein. The latest issue of SAE publications shall apply.

2.1.1 SAE Publications

Available from SAE, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or 724-776-4970 (outside USA), www.sae.org.

- SAE J1409 Air Brake Valves Test Procedure
- SAE J1410 Air Brake Valve—Performance Requirements
- SAE HS 806 Oil Filter Test Procedure

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2013 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/J2024_201305**

2.1.2 Federal Specification

Available from U.S. Government, DODSSP, Subscription Services Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094, Tel: 215-697-2179, <http://assist.daps.mil> or <http://stinet.dtic.mil>.

Federal Specification F-F-351c

3. FORMULA FOR CONTAMINATED OIL TO BE USED AS A LUBRICANT WHEN TESTING VEHICLE AIR COMPRESSORS

Contaminated oil mixture consists of 11 parts SAE 15W40CD type oil or most current API certified oil (i.e. CJ) to 1 part SOFTC-2A contaminant. Contaminant SOFTC-2A is available from Powder Technology Inc., P.O. Box 1464, Burnsville, MN 55337.

SOFTC-2A is specified per SAE Oil Filter Procedure HS 806. SAE HS 806 Specification references federal specification F-F-351c formulation procedure.

Ingredients of SOFTC-2A as specified are as follows in Table 1:

TABLE 1 - SOFTC-2A INGREDIENTS

Ingredients	Weight
Carbon Black	16% by weight
Ferric Oxide	2% by weight
PV Resin	4% by weight
Straight Mineral Oil	<u>78%</u> by weight
	100%

The formulation in Table 1 reflects the use in modern trucks of multiviscosity oil with its additive packages. Also included are rust, abrasive ingredients, and road contaminants which find their way into the engine crankcase by fuel combustion or by air drawn into the engine. The combination can accelerate air compressor wear and can cause carbon build-up.

4. FORMULA FOR A UNIFORM CONTAMINANT WHEN DURABILITY TESTING VEHICLE PNEUMATIC SYSTEM COMPONENTS OTHER THAN COMPRESSORS

The formula for a uniform contaminant is listed in 4a, b, and c. This formulation was developed to reflect the oil, abrasive dirt, and water that often find their way into the various pneumatic components. This combination can cause wear and corrosion and often can swell, shrink, or degrade the nonmetallic materials used in these devices.

- a. 1 g of Arizona dust, coarse
- b. 900 mL of SOFTC-2A contaminant
- c. 1800 mL water

When the effect of multiviscosity oil additives is desired in the testing of vehicle pneumatic system components, the addition of SAE 15W40CD type oil may be considered. This addition to the formulation, however, should be clearly noted in the test results.

5. OTHER CONTAMINANTS

In addition, various components of the pneumatic systems being tested may be immersed in other specific chemicals to test for the effect of these contaminants on the materials used to produce the devices. Such chemicals may include, but not be limited to, methyl alcohol (usually water and 97% to 100% methyl alcohol); denatured ethyl alcohol (often labeled methyl hydrate for Canadian Federal Government regulations); and reservoir drainings. A recommended recipe for a synthetic formulation reservoir draining is: