



SURFACE VEHICLE STANDARD



J2299 JAN2012

Issued 1996-09
Stabilized 2012-01

Superseding J2299 SEP1996

Ultraviolet Leak Detection: Performance Requirements for Fluorescent Refrigerant Leak Detection Dye Injection Equipment for Aftermarket Service of Mobile Air-Conditioning Systems

RATIONALE

Technology is stable and no change is expected.

STABILIZED NOTICE

This document has been declared "Stabilized" by the SAE Interior Climate Control Committee and will no longer be subjected to periodic reviews for currency. Users are responsible for verifying references and continued suitability of technical requirements. Newer technology may exist.

SAE Technical Standards Board Rules provide that: "This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user."

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2012 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

TO PLACE A DOCUMENT ORDER: Tel: 877-606-7323 (inside USA and Canada)
Tel: +1 724-776-4970 (outside USA)
Fax: 724-776-0790
Email: CustomerService@sae.org
http://www.sae.org

SAE WEB ADDRESS:

**SAE values your input. To provide feedback
on this Technical Report, please visit
http://www.sae.org/technical/standards/J2299_201201**