

Second edition  
2022-10

---

---

---

**Measurement of fluid flow by means of  
pressure differential devices inserted  
in circular cross-section conduits  
running full —**

**Part 6:  
Wedge meters**

*Mesurage de débit des fluides au moyen d'appareils déprimogènes  
insérés dans des conduites en charge de section circulaire —*

*Partie 6: Débitmètres à coin*



Reference number  
ISO 5167-6:2022(E)



**COPYRIGHT PROTECTED DOCUMENT**

© ISO 2022

All rights reserved. Unless otherwise specified, or required in the context of its implementation, no part of this publication may be reproduced or utilized otherwise in any form or by any means, electronic or mechanical, including photocopying, or posting on the internet or an intranet, without prior written permission. Permission can be requested from either ISO at the address below or ISO's member body in the country of the requester.

ISO copyright office  
CP 401 • Ch. de Blandonnet 8  
CH-1214 Vernier, Geneva  
Phone: +41 22 749 01 11  
Email: [copyright@iso.org](mailto:copyright@iso.org)  
Website: [www.iso.org](http://www.iso.org)

Published in Switzerland

# Contents

|   | Page      |
|---|-----------|
| <b>Foreword</b>   | <b>iv</b> |
| <b>Introduction</b>   | <b>v</b>  |
| <b>1 Scope</b>  | <b>1</b>  |
| <b>2 Normative references</b>   | <b>1</b>  |
| <b>3 Terms and definitions</b>  | <b>1</b>  |
| <b>4 Principles of the method of measurement and computation</b>  | <b>2</b>  |
| <b>5 Wedge meters</b>   | <b>3</b>  |
| 5.1 Field of application  | 3         |
| 5.2 General shape   | 4         |
| 5.3 Material and manufacture  | 5         |
| 5.4 Pressure tappings   | 5         |
| 5.5 Discharge coefficient, $C$  | 6         |
| 5.5.1 Limits of use   | 6         |
| 5.5.2 Discharge coefficient of the wedge meter  | 6         |
| 5.6 Expansibility [expansion] factor, $\varepsilon$   | 6         |
| 5.7 Uncertainty of the discharge coefficient, $C$   | 7         |
| 5.8 Uncertainty of the expansibility [expansion] factor, $\varepsilon$  | 7         |
| 5.9 Pressure loss   | 7         |
| <b>6 Installation requirements</b>  | <b>7</b>  |
| 6.1 General   | 7         |
| 6.2 Minimum upstream and downstream straight lengths for installations between various fittings and the wedge meter | 7         |
| 6.3 Additional specific installation requirements for wedge meters  | 8         |
| 6.3.1 Circularity and cylindricality of the pipe  | 8         |
| 6.3.2 Roughness of the upstream and downstream pipe   | 8         |
| 6.3.3 Positioning of a thermowell   | 8         |
| 6.3.4 Bidirectional wedge meters  | 9         |
| <b>7 Flow calibration of wedge meters</b>   | <b>9</b>  |
| 7.1 General   | 9         |
| 7.2 Test facility   | 9         |
| 7.3 Meter installation  | 9         |
| 7.4 Design of the test programme  | 9         |
| 7.5 Reporting the calibration results   | 10        |
| 7.6 Uncertainty analysis of the calibration   | 10        |
| 7.6.1 General   | 10        |
| 7.6.2 Uncertainty of the test facility  | 10        |
| 7.6.3 Uncertainty of the discharge coefficient of the wedge meter   | 10        |
| <b>Annex A (informative) Table of expansibility [expansion] factor</b>  | <b>11</b> |
| <b>Annex B (informative) Use of <math>Kd^2</math> parameter</b>   | <b>12</b> |
| <b>Bibliography</b>   | <b>13</b> |