



Standard Test Method for Shrinkage Factors of Soils by the Wax Method¹

This standard is issued under the fixed designation D4943; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reappraisal.

1. Scope*

1.1 This test method covers the procedure for determining the shrinkage limit of soils.

1.2 The data obtained using this test method may also be used to calculate shrinkage ratio, volumetric shrinkage, and linear shrinkage.

1.3 This test method is applicable only for cohesive soils.

1.4 Since this test method is performed only on that portion of a soil which passes the No. 40 (425- μ m) sieve, the relative consistency of this portion of the soil to the properties of the sample as a whole must be considered when using these procedures to evaluate the properties of a soil.

1.5 The shrinkage limit along with the liquid limit and plastic limit of soils are often collectively referred to as the Atterberg limits in recognition of their formation by Swedish soil scientist, A. Atterberg. These limits distinguish the boundaries of the several consistency states of cohesive soils.

1.6 All recorded and calculated values shall conform to the guide for significant digits and rounding established in Practice D6026.

1.6.1 The procedures used to specify how data are collected/recorded and calculated in this standard are regarded as the industry standard. In addition, they are representative of the significant digits that should generally be retained. The procedures used do not consider material variation, purpose for obtaining the data, special purpose studies, or any considerations for the user's objectives; and it is common practice to increase or reduce significant digits of reported data to be commensurate with these considerations. It is beyond the scope of this standard to consider significant digits used in analysis methods for engineering design.

1.7 The values stated in SI units are to be regarded as standard. No other units of measurement are included in this standard.

¹ This test method is under the jurisdiction of ASTM Committee D18 on Soil and Rock and is the direct responsibility of Subcommittee D18.03 on Texture, Plasticity and Density Characteristics of Soils.

Current edition approved June 1, 2008. Published July 2008. Originally approved in 1989. Last previous edition approved in 2002 as D4943 – 02. DOI: 10.1520/D4943-08.

1.8 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety and health practices and determine the applicability of regulatory limitations prior to use.* For specific safety hazards, see Section 7 and Note 4.

2. Referenced Documents

2.1 *ASTM Standards:*²

C670 Practice for Preparing Precision and Bias Statements for Test Methods for Construction Materials

C702 Practice for Reducing Samples of Aggregate to Testing Size

D75 Practice for Sampling Aggregates

D420 Guide to Site Characterization for Engineering Design and Construction Purposes (Withdrawn 2011)³

D653 Terminology Relating to Soil, Rock, and Contained Fluids

D854 Test Methods for Specific Gravity of Soil Solids by Water Pycnometer

D3740 Practice for Minimum Requirements for Agencies Engaged in Testing and/or Inspection of Soil and Rock as Used in Engineering Design and Construction

D4318 Test Methods for Liquid Limit, Plastic Limit, and Plasticity Index of Soils

D4753 Guide for Evaluating, Selecting, and Specifying Balances and Standard Masses for Use in Soil, Rock, and Construction Materials Testing

D6026 Practice for Using Significant Digits in Geotechnical Data

E2251 Specification for Liquid-in-Glass ASTM Thermometers with Low-Hazard Precision Liquids

E11 Specification for Woven Wire Test Sieve Cloth and Test Sieves

3. Terminology

3.1 *Definitions*—All definitions are in accordance with Terminology D653.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

*A Summary of Changes section appears at the end of this standard

4. Summary of Test Method

4.1 A sample of fine-grained soil is thoroughly remolded with water to form a paste that is at approximately the liquid limit consistency. This paste is used to fill a small dish to form a soil pat. The initial moisture content of the wet soil pat is determined. The soil pat is slowly dried to constant mass. The volume of the dry soil is determined using a water submersion technique. A coating of wax is used to prevent water absorption by the dry soil pat. Then the moisture-content loss to dry the soil to a constant volume is determined and subtracted from the initial moisture content to calculate the shrinkage limit. The measurements are used to compute the soil constants.

5. Significance and Use

5.1 The term shrinkage limit, expressed as a moisture content in percent to the nearest whole number, represents the amount of water required just to fill all of the voids of a given cohesive soil at its minimum void ratio obtained by oven-drying. The shrinkage limit can be used to evaluate the shrinkage potential, crack development potential, and swell potential of earthwork involving cohesive soils.

NOTE 1—The quality of the result produced by this standard is dependent on the competence of the personnel performing it, and the suitability of the equipment and facilities used. Agencies that meet the criteria of Practice D3740 are generally considered capable of competent and objective testing/sampling/inspection/and the like. Users of this standard are cautioned that compliance with Practice D3740 does not in itself assure reliable results. Reliable results depend on many factors; Practice D3740 provides a means of evaluating some of those factors.

6. Apparatus

6.1 *Balance or Scale*—A balance or scale having a minimum capacity of 500 g and meeting the requirements of Specification D4753 for a balance of 0.01-g readability.

6.2 *Suspension Apparatus (optional)*—A device centered on the balance suitable for suspending the soil specimen in a container of water located next to or below the balance or scale.

6.3 *Dish, Shrinkage*—A circular porcelain or monel metal milk dish having a flat bottom about 40 to 45 mm in diameter and about 12 to 15 mm deep.

6.4 *Drying Oven*—An oven, thermostatically controlled, preferably of the forced draft type, and capable of maintaining a uniform temperature of $110 \pm 5^\circ\text{C}$ throughout the drying chamber.

6.5 *Humidity Enclosure (optional)*—Small closed container large enough for shrinkage dishes and a small container of water used in dry climates to slow the initial rate of drying.

6.6 *Mortar and Pestle*—Mortar, iron or porcelain, about 125 to 150-mm diameter with rubber tipped pestle.

6.7 *Spatula*—A spatula or pill knife having a blade about 100 mm long by about 20 mm wide.

6.8 *Straightedge*—A stiff metal straightedge of convenient length. The scraping edge must be beveled if it is thicker than 3 mm.

6.9 *Sieve*—U.S.A. Standard series No. 40 (425- μm) sieve conforming to the requirements of Specification E11.

6.10 *Wax*—Microcrystalline or other suitable wax mixture which is not brittle when dry and does not shrink during solidification. Sufficient quantity when melted in the wax warmer to submerge the soil pat.

NOTE 2—A 50/50 mixture of paraffin wax and petroleum jelly will provide an adequate alternative.

6.11 *Sewing Thread*—Fine thread to hold the specimen to dip into the wax.

6.12 *Water*, distilled.

6.13 *Water Bath*—Of sufficient size (for example, 250 mL beaker) to submerge the soil pat when determining indicated mass in water.

6.14 *Wax Warmer*—Sufficient temperature control to avoid overheating.

6.15 *Thermometer (optional)*—A thermometer, in the room temperature range, 0.5° gradations, conforming to the requirements of Specification E2251.

6.16 *Glass or Clear Plastic Plate*, used for calibrating the shrinkage dish, about 80 by 80 mm, about 5 mm thick.

6.17 *Petroleum Base Lubricant*, used to grease the shrinkage dish.

6.18 *Liquid Limit Device and Grooving Tool*, as described in Test Method D4318.

7. Safety Hazards

7.1 Wax melting equipment or hot wax may burn unprotected skin. Overheated wax may burst into flames; therefore, extreme care should be taken when working with hot wax. Do not use an open flame device to heat wax.

8. Sampling

8.1 Take samples from any location that satisfies testing needs. However, use Practices C702 and D75, as well as Guide D420, as guides for selecting and preserving samples from various types of sampling operations.

8.2 Where sampling operations have preserved the natural stratification of a sample, keep the various strata separated and perform tests on the particular stratum of interest with as little contamination as possible from other strata. Where a mixture of materials will be used in construction, combine the various components in such proportions that the resultant sample represents the actual construction case.

8.3 Where data from this test method are to be used for correlation with other laboratory or field test data, use the same material as used for these tests where possible.

8.4 Obtain a representative portion from the total sample sufficient to provide 150 to 200 g of material passing the No. 40 (425- μm) sieve. Mix samples thoroughly in a pan with a spatula or scoop and scoop a representative portion from the total mass by making one or more sweeps with a scoop through the mixed mass.

9. Calibration and Standardization

9.1 Calibrate each shrinkage dish used in accordance with Annex A1. Since the dishes may have different volumes, each dish must be permanently identified.