



# Standard Terminology Relating to Protective Clothing<sup>1</sup>

This standard is issued under the fixed designation F1494; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reappraisal. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reappraisal.

## 1. Scope

1.1 This standard defines the specialized terms used in standards developed by Committee F23 on Protective Clothing.

1.2 Definitions of Terms, which were drafted for use only in a single standard, are also included for convenient reference. Under ASTM rules they may become full definitions in the future, if they are used in additional standards.

1.3 Additional terminology relevant to protective clothing and to the components of protective clothing can be found in Terminology [D123](#), [D1566](#), and [D4805](#).

## 2. Referenced Documents

### 2.1 *ASTM Standards*:<sup>2</sup>

[D123 Terminology Relating to Textiles](#)

[D1566 Terminology Relating to Rubber](#)

[D4805 Terminology for Plastics Standards \(Withdrawn 2002\)](#)<sup>3</sup>

[F739 Test Method for Permeation of Liquids and Gases through Protective Clothing Materials under Conditions of Continuous Contact](#)

[F903 Test Method for Resistance of Materials Used in Protective Clothing to Penetration by Liquids](#)

[F955 Test Method for Evaluating Heat Transfer through Materials for Protective Clothing Upon Contact with Molten Substances](#)

[F1002 Performance Specification for Protective Clothing and Materials for Use by Workers Exposed to Specific Molten Substances and Related Thermal Hazards](#)

[F1060 Test Method for Thermal Protective Performance of Materials for Protective Clothing for Hot Surface Contact](#)

[F1154 Practices for Qualitatively Evaluating the Comfort, Fit, Function, and Durability of Protective Ensembles and Ensemble Components](#)

[F1291 Test Method for Measuring the Thermal Insulation of Clothing Using a Heated Manikin](#)

[F1358 Test Method for Effects of Flame Impingement on Materials Used in Protective Clothing Not Designated Primarily for Flame Resistance](#)

[F1359 Test Method for Liquid Penetration Resistance of Protective Clothing or Protective Ensembles Under a Shower Spray While on a Mannequin](#)

[F1383 Test Method for Permeation of Liquids and Gases through Protective Clothing Materials under Conditions of Intermittent Contact](#)

[F1407 Test Method for Resistance of Chemical Protective Clothing Materials to Liquid Permeation—Permeation Cup Method](#)

[F1414 Test Method for Measurement of Cut Resistance to Chain Saw in Lower Body \(Legs\) Protective Clothing](#)

[F1449 Guide for Industrial Laundering of Flame, Thermal, and Arc Resistant Clothing](#)

[F1458 Test Method for Measurement of Cut Resistance to Chain Saw of Foot Protective Devices](#)

[F1461 Practice for Chemical Protective Clothing Program](#)

[F1494 Terminology Relating to Protective Clothing](#)

[F1670 Test Method for Resistance of Materials Used in Protective Clothing to Penetration by Synthetic Blood](#)

[F1671 Test Method for Resistance of Materials Used in Protective Clothing to Penetration by Blood-Borne Pathogens Using Phi-X174 Bacteriophage Penetration as a Test System](#)

[F1731 Practice for Body Measurements and Sizing of Fire and Rescue Services Uniforms and Other Thermal Hazard Protective Clothing](#)

[F1818 Specification for Foot Protection for Chain Saw Users](#)

[F1819 Test Method for Resistance of Materials Used in Protective Clothing to Penetration by Synthetic Blood Using a Mechanical Pressure Technique](#)

[F1862 Test Method for Resistance of Medical Face Masks to Penetration by Synthetic Blood \(Horizontal Projection of Fixed Volume at a Known Velocity\)](#)

[F1897 Specification for Leg Protection for Chain Saw Users](#)

[F2061 Practice for Chemical Protective Clothing: Wearing, Care, and Maintenance Instructions](#)

<sup>1</sup> This terminology is under the jurisdiction of ASTM Committee F23 on Personal Protective Clothing and Equipment and is the direct responsibility of Subcommittee F23.91 on Editorial.

Current edition approved Oct. 1, 2014. Published November 2014. Originally approved in 1993. Last previous edition approved in 2013 as F1494 – 13. DOI: 10.1520/F1494-14.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, [www.astm.org](http://www.astm.org), or contact ASTM Customer Service at [service@astm.org](mailto:service@astm.org). For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

<sup>3</sup> The last approved version of this historical standard is referenced on [www.astm.org](http://www.astm.org).

**F2101** Test Method for Evaluating the Bacterial Filtration Efficiency (BFE) of Medical Face Mask Materials, Using a Biological Aerosol of *Staphylococcus aureus*

**F2300** Test Method for Measuring the Performance of Personal Cooling Systems Using Physiological Testing

**F2302** Performance Specification for Labeling Protective Clothing as Heat and Flame Resistant

**F2407** Specification for Surgical Gowns Intended for Use in Healthcare Facilities

**F2668** Practice for Determining the Physiological Responses of the Wearer to Protective Clothing Ensembles

**F2669** Performance Specification for Protective Clothing Worn by Operators Applying Pesticides

**F2733** Specification for Flame Resistant Rainwear for Protection Against Flame Hazards

**F2815** Practice for Chemical Permeation through Protective Clothing Materials: Testing Data Analysis by Use of a Computer Program

**F2894** Test Method for Evaluation of Materials, Protective Clothing and Equipment for Heat Resistance Using a Hot Air Circulating Oven

### 3. Terminology

#### 3.1 Definitions:

**acclimation**, *n*—physiological adaptations occurring within an organism, which reduce the strain or enhance endurance of strain, caused by artificially or experimentally induced stressful changes in particular environmental conditions. (F23.60) **F2300, F2668**

**acclimatization**, *n*—physiological adaptations occurring within an organism, which reduce the strain or enhance endurance of strain, caused by stressful changes in the natural environment. (F23.60) **F2300, F2668**

**after-flame time**, *n*—the length of time for which a material continues to flame after the ignition source has been removed. (F23.20) **F1358**

**afterglow**, *n*—a glow in a material after the removal of an external ignition source or after the cessation (natural or induced) of flaming of the material (see also **glow**). (F23.20) **F1358**

**agar**, *n*—a semisolid culture medium used to support the growth of bacteria and other micro-organisms. (F23.40) **F1671**

**analytical detection limit**, *n*—a number, expressed in units of concentration (or amount), that describes the lowest concentration level (or amount) that an analyst can determine to be different from an analytical blank (background level). (F23.70) **F1461**

**airborne exposure pathways**, *n*—inhalation routes of exposure to the medical face mask wearer.

**analytical technique**, *n*—a procedure whereby the concentration of the test chemical in a collection medium is quantitatively determined. (F23.30) **F739**

**anisotropic**, *adj*—having different values for a specific property in different directions. (F23.20) **F1358**

**armhole**, *n*—*in garment construction*, the area of a garment through which the arm passes or into which a sleeve is fitted. (See **armscye**.) (F23.60) **F1731**

**armscye**, *n*—*in garment construction*, the opening in a garment for the attachment of a fitted sleeve. (See **armhole**.) (F23.60) **F1731**

**aseptic**, *adj*—sterile, free from viable microbiological contamination. (F23.40) **F1671**

**assay**, *n*—analysis of a mixture to determine the presence or concentration of a particular component. (F23.40) **F1671**

**assay fluid**, *n*—a sterile liquid used to wash the test specimen surface to determine microbiological penetration. (F23.40) **F1671**

**authority having jurisdiction**, *n*—the organization, office, or individual responsible for approving any equipment, installation, or procedure. (F23.20) **F1818**

**back waist length**, *n*—*in body measurements*, the vertical distance along the spine from the cervical to the waist. (F23.60) **F1731**

**bacterial filtration efficiency (BFE)**, *n*—the effectiveness of medical face mask material in preventing the passage of aerosolized bacteria; expressed in the percentage of a known quantity that does not pass the medical face mask material at a given aerosol flow rate.

**bacteriophage**, *n*—a type of virus which infects bacteria. (F23.40) **F1671**

**bartack**, *n*—*in garment construction*, a reinforcement at points of strain. (F23.60) **F1731**

**biological aerosol**, *n*—a suspension of particles containing biological agents which have been dispersed in a gas. (F23.40) **F2101**

**biological monitoring**, *n*—the chemical analysis of chemicals or metabolites, or both, from a worker's blood, urine, fingernails, sweat, breath, and so forth. (F23.70) **F1461**

**blood-borne pathogen**, *n*—an infectious bacterium or virus, or other disease-inducing microbe carried in blood or other potentially infectious body fluids. (F23.40) **F1671, F1819, F1862, F2101, F2407**

**body dimension**, *n*—*in garment construction*, a body measurement which can be used to build a sizing system or to select an appropriately sized garment. (F23.60) **F1731**

**body fluid**, *n*—any liquid produced, secreted, or excreted by the human body.

**body fluid simulant**, *n*—a liquid which is used to act as a model for human body liquids. (F23.40) **F1670, F1671**

**body measurement**, *n*—*in anthropometry*, a standardized distance between two specified points on the human anatomy. (F23.60) **F1731**

- break-open**—in testing thermal protective material, a response evidenced by the formation of a hole in the material, which allows the molten substance to pass through the material. (F23.80) **F955**
- breakthrough detection time**, *n*—the elapsed time measured from the start of the test to the sampling time that immediately precedes the sampling time at which the test chemical is first detected. (F23.30) **F739, F1383**
- buddy system**, *n*—a means of organizing employee work groups whereby each participant is matched with another so that prompt assistance can be rendered in the case of any emergency. (F23.70) **F1461**
- burn distance**, *n*—the measurement from the bottom edge of the specimen to the farthest point that shows evidence of damage due to combustion. (F23.20) **F1358**
- burning behavior**, *n*—all the changes that take place when materials or products are exposed to a specified ignition source. (F23.20) **F1358**
- bust girth**, *n*—*in body measurement*, the circumference of the body over the fullest part of the breasts and parallel to the floor. (See **chest girth**.) (F23.60) **F1731**
- care and maintenance**, *n*—effective cleaning to remove soil and maximize use life of garments while maintaining (not removing) protective properties. (F23.80) **F1449**
- centerline**, *n*—*in foot protective devices*, a line which extends from the toe of the footwear horizontally along the sole to the heel vertically to the top of the footwear, and diagonally to the point of intersection at the toe. (F23.20) **F1458**
- certification**, *n*—a system whereby an organization determines that a manufacturer has demonstrated the ability to make a product that complies with the requirements of the specification, authorizes the manufacturer to use a label on products that comply with the requirements of the specification, and conducts a follow-up program to verify the methods the manufacturer uses to determine compliance with the requirements of this specification. (F23.20) **F1818**
- certification organization**, *n*—an independent, third party organization that determines product compliance with the requirements of the specification with a labeling and listing follow-up program. (F23.20) **F1818**
- cervical**, *n*—*in body measurements*, the most prominent bone at the base of the neck. (F23.60) **F1731**
- chain saw**, *n*—a portable power operated tool used for cutting wood which has cutters linked in a chain. (F23.20) **F1414, F1458**
- chain speed**, *n*—the velocity of synchronized movement of linked cutters around a bar and sprocket. (F23.20) **F1414, F1458**
- chainspeed 50 (CS50)**, *n*—*for chain saw protection*, the mean velocity at which cut through occurs. (F23.20) **F1458, F1818, F1897**
- chainstop**, *n*—*for chainsaw cut resistance*, the resulting action when a material clogs (jams) the drive sprocket or slows the speed sufficiently to prevent advancement of the chain saw. (F23.20) **F1414, F1458, F1818**
- challenge suspension**, *n*—a liquid containing an agent that is used to test the penetration resistance of materials. (F23.40) **F1671**
- char length**, *n*—in measuring flame resistance of textiles, the distance from the fabric edge which was directly exposed to the flame to the furthest point of visible fabric damage after a specified tearing force has been applied. (F23.80) **F2302, F2733**
- charring**—the formation of a carbonaceous residue as the result of pyrolysis or incomplete combustion. (F23.80) **F1060**
- chemical protective clothing (CPC)**, *n*—any material or combination of materials used in an item of clothing for the purpose of isolating parts of the body from direct contact with a potentially hazardous chemical. (F23.70) **F1461**
- chemical-protective suit ensemble**—the combination of protective clothing with respiratory protective equipment, hoods, helmets, gloves, boots, communications systems, cooling devices, and other accessories intended to protect the wearer from a chemical hazard when worn together. (F23.50) **F1154, F1359**
- chest**, *n*—*in garment construction*, a measurement taken from below each armhole seam straight across the garment while it is laid flat. (F23.60) **F1731**
- chest girth**, *n*—*in body measurements*, the circumference of the body over the shoulder blades, under the arms and across the upper chest. (See **bust girth**.) (F23.60) **F1731**
- clo**, *n*—a unit of thermal resistance (insulation) equal to 0.155 K-m<sub>2</sub>/W. (F23.60) **F1291**  
DISCUSSION—The value of the clo was selected as roughly the insulation value of typical indoor clothing, which should keep a resting man (producing heat at the rate of 58 W/m<sub>2</sub>) comfortable in an environment at 21°C, air movement 0.1 m/s.
- closed-loop**, *adj*—refers to a testing mode in which there is no change in the volume of the collection medium except for sampling. (F23.30) **F739, F1383**
- clothing ensemble**, *n*—a group of garments worn together on the body at the same time. (F23.60) **F1291**
- collection medium**, *n*—a liquid, gas, or solid that absorbs, adsorbs, dissolves, suspends, or otherwise captures the test chemical and does not affect the measured permeation. (F23.30) **F739, F1383**
- combustion**, *n*—a chemical process of oxidation that occurs at a rate fast enough to produce heat and usually light either as glow or flames. (F23.20) **F1358**
- contact time**, *n*—*in an intermittent contact test*, the duration during each cycle that the challenge side chamber of the permeation cell is filled with the test chemical. (F23.30) **F1383**