



# SURFACE VEHICLE RECOMMENDED PRACTICE

J1319™

AUG2022

Issued 1987-08  
Revised 2022-08

Superseding J1319 OCT2015

## Rear Fog Lamp System

### RATIONALE

The following updates were made during the Five-Year Review of this SAE Recommended Practice:

- Section 2.1.1 SAE Publications updated to reflect new title for SAE J578.
- SAE J1889 moved to 2.1.1 from 2.2.1, and SAE J1889 inserted as new requirement in 5.1.5.2.
- Section 2.1.2 title updated to “United Nations Publications” from “ECE Publication.”
- SAE J567 moved to 2.2.1 from 2.1.1, and SAE J387 added to 2.2.1.
- UN Regulation 148 added to the Foreword and 2.1.2 United Nations Publications.
- Section 3.3 title revised to LIGHT EMITTING DIODE (LED) was L.E.D.
- Section 5.3 added to clarify materials test SAE J576 is part of this report.
- Figure 1 revised by replacing arrows with dots to clarify the extents of H-Line A and V-Line B, and the associated footnote 2 revised to “... along entire lengths between end points of H-Line A and V-Line B...”
- Previous 7.1.3 combined into 7.2, subsequent sections renumbered.
- Section 7.2 reworded to align more closely with the electrical connection requirements stated in UN Regulation 48.

### FOREWORD

“UN Regulation 38 - Uniform Provisions Concerning the Approval of Rear Fog Lamps for Power-Driven Vehicles and Their Trailers” and/or “UN Regulation 148 - Uniform Provisions Concerning the Approval of Light-Signaling Devices (Lamps) for Power Driven Vehicles and their Trailers” are similar to this SAE Recommended Practice. Rear fog lamp minimum photometric candela values are lower in this SAE Recommended Practice than those specified in UN Regulations to account for the differences between UN test voltage versus SAE design voltage when incandescent light sources are utilized in rear fog lamps. Maximum photometric candela values in this SAE Recommended Practice are common with those found in UN Regulations to account for rear fog lamps utilizing LED light sources.

SAE Executive Standards Committee Rules provide that: “This report is published by SAE to advance the state of technical and engineering sciences. The use of this report is entirely voluntary, and its applicability and suitability for any particular use, including any patent infringement arising therefrom, is the sole responsibility of the user.”

SAE reviews each technical report at least every five years at which time it may be revised, reaffirmed, stabilized, or cancelled. SAE invites your written comments and suggestions.

Copyright © 2022 SAE International

All rights reserved. No part of this publication may be reproduced, stored in a retrieval system or transmitted, in any form or by any means, electronic, mechanical, photocopying, recording, or otherwise, without the prior written permission of SAE.

**TO PLACE A DOCUMENT ORDER:** Tel: 877-606-7323 (inside USA and Canada)  
Tel: +1 724-776-4970 (outside USA)  
Fax: 724-776-0790  
Email: CustomerService@sae.org  
http://www.sae.org

SAE WEB ADDRESS:

For more information on this standard, visit  
[https://www.sae.org/standards/content/J1319\\_202208/](https://www.sae.org/standards/content/J1319_202208/)

## 1. SCOPE

This SAE Recommended Practice provides test procedures, requirements, and guidelines for rear fog lamp systems.

## 2. REFERENCES

### 2.1 Applicable Documents

The following publications form a part of this specification to the extent specified herein. Unless otherwise indicated, the latest issue of SAE publications and the latest revision of referenced UN Regulations shall apply.

#### 2.1.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or +1 724-776-4970 (outside USA), [www.sae.org](http://www.sae.org).

SAE J575	Test Methods and Equipment for Lighting Devices for Use on Vehicles Less than 2032 mm in Overall Width
SAE J576	Plastic Material or Materials for Use in Optical Parts Such as Lenses and Reflex Reflectors of Motor Vehicle Lighting Devices
SAE J578	Chromaticity Requirements for Ground Vehicle Lamps and Lighting Equipment
SAE J585	Tail Lamps (Rear Position Lamps) for Use on Motor Vehicles Less than 2032 mm in Overall Width
SAE J759	Lighting Identification Code
SAE J1889	LED Signal and Marking Lighting Devices

#### 2.1.2 United Nations Publications

Available from United Nations Economic Commission for Europe, Palais des Nations, CH-1211, Geneva 10, Switzerland, Tel: +41-0-22-917-12-34, <https://www.unece.org/transport/vehicle-regulations>.

UN Regulation 38	Uniform Provisions Concerning the Approval of Rear Fog Lamps for Power-Driven Vehicles and Their Trailers
UN Regulation 48	Uniform Provisions Concerning the Approval of Vehicles with Regard to the Installation of Lighting and Light-Signaling Devices
UN Regulation 148	Uniform Provisions Concerning the Approval of Light-Signaling Devices (Lamps) for Power-Driven Vehicles and Their Trailers

## 2.2 Related Publications

The following publications are provided for information purposes only and are not a required part of this SAE Technical Report.

### 2.2.1 SAE Publications

Available from SAE International, 400 Commonwealth Drive, Warrendale, PA 15096-0001, Tel: 877-606-7323 (inside USA and Canada) or +1 724-776-4970 (outside USA), [www.sae.org](http://www.sae.org).

SAE J387	Terminology - Motor Vehicle Lighting
SAE J567	Light Source Retention System
SAE J2139	Tests for Signal and Marking Devices Used on Vehicles 2032 mm or More in Overall Width