Australian Standard®

Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels

Part 3: Fittings and saddles for a maximum operating pressure of 1 bar (100 kPa)



This Australian Standard® was prepared by Committee PL-021, PVC, ABS and Polyamide Pipe Systems. It was approved on behalf of the Council of Standards Australia on 9 March 2007.

This Standard was published on 12 July 2007.

The following are represented on Committee PL-021:

- Australian Chamber of Commerce and Industry
- CSIRO Manufacturing and Materials Technology
- Certification Interests
- Energy Networks Association
- Engineers Australia
- Local Government New Zealand
- Master Plumbers, Gasfitters and Drainlayers New Zealand
- New Zealand Water and Waste Association
- Plastic Industry Pipe Association of Australia
- Plastics New Zealand
- Water Services Association of Australia

This Standard was issued in draft form for comment as DR 06622.

Standards Australia wishes to acknowledge the participation of the expert individuals that contributed to the development of this Standard through their representation on the Committee and through public comment period.

Keeping Standards up-to-date

Australian Standards® are living documents that reflect progress in science, technology and systems. To maintain their currency, all Standards are periodically reviewed, and new editions are published. Between editions, amendments may be issued.

Standards may also be withdrawn. It is important that readers assure themselves they are using a current Standard, which should include any amendments that may have been published since the Standard was published.

Detailed information about Australian Standards, drafts, amendments and new projects can be found by visiting **www.standards.org.au**

Standards Australia welcomes suggestions for improvements, and encourages readers to notify us immediately of any apparent inaccuracies or ambiguities. Contact us via email at mail@standards.org.au, or write to Standards Australia, GPO Box 476, Sydney, NSW 2001.

Australian Standard®

Buried, high-impact poly(vinyl chloride) (PVC-HI) piping systems for the supply of gaseous fuels

Part 3: Fittings and saddles for a maximum operating pressure of 1 bar (100 kPa)

First published as AS 1464.1—1974 and AS 1464.2—1974. Second edition 1984. Replaced by AS ISO 6993.3—2007.

COPYRIGHT

© Standards Australia

All rights are reserved. No part of this work may be reproduced or copied in any form or by any means, electronic or mechanical, including photocopying, without the written permission of the publisher.

Published by Standards Australia GPO Box 476, Sydney, NSW 2001, Australia ISBN 0 7337 8180 2