

## STANDARDS AUSTRALIA

**Amendment No. 1**  
to  
**AS 4145.1—2008**  
**Locksets and hardware for doors and windows**  
**Part 1: Glossary of terms and rating system**

**CORRECTION**

The 2008 edition of AS 4145.1 is amended as follows; the amendments should be inserted in the appropriate places.

SUMMARY: This Amendment applies to the Tables 3.3 and 3.5 and Appendix B.

Published on 2 December 2009.

AMDT  
No. 1  
DEC  
2009

**Table 3.3**

In the second row, under Column Heading ‘**Sc9**’ *delete* ‘N/A’ and *replace* with ‘100 000+’

AMDT  
No. 1  
DEC  
2009

**Table 3.5**

- 1 In row commencing ‘Resistance of bolt to horizontal impact’ under Column heading ‘**S<sub>L6</sub>**’ *delete* existing text and *replace* with ‘2 × 60 J blows’.
- 2 *Delete* the values in row commencing ‘Resistance of knob to axial load $\ddagger$ ’ and *replace* with the following:

N/A	N/A	1.1 kN	1.1 kN	1.4 kN	1.5 kN	2.0 kN	2.3 kN	N/A	N/A
-----	-----	--------	--------	--------	--------	--------	--------	-----	-----

- 3 *Delete* the values in row commencing ‘Resistance of cylinder to vertical impact attached to lockset’

N/A	N/A	1 × 20 J blow	1 × 20 J blow	2 × 20 J blows	2 × 20 J blows	5 × 20 J blows	15 × 20 J blows	N/A	N/A
-----	-----	------------------	------------------	-------------------	-------------------	-------------------	--------------------	-----	-----

AMDT  
No. 1  
DEC  
2009

**Appendix B**

In Item (b) in the first paragraph, *delete* ‘Lockset’ and *replace* with ‘Lock’.