



Designation: A1075 – 12 (Reapproved 2022)

Standard Specification for Flanged Steel U-Channel Posts¹

This standard is issued under the fixed designation A1075; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This specification covers flanged U-channel carbon steel posts having a nominal weight ranging from 0.75 lb/ft to 6.0 lb/ft and a nominal width ranging from 1.25 in. to 4.0 in. These posts are furnished in the as-wrought condition intended for applications requiring high tensile strength or crashworthiness and with a lower carbon (LC) designation for use where higher ductility or improved weldability are required. These materials are available in multiple yield strength levels of 50 ksi, 60 ksi, 70 ksi, and 80 ksi (345 MPa, 420 MPa, 485 MPa, and 550 MPa). The 50 ksi and 60 ksi (345 MPa and 420 MPa) yield strength grades are available as lower carbon posts, designated as Grades 50LC or 60LC.

NOTE 1—This specification does not cover high-strength low-alloy (HSLA) post. Refer to Specification [A572/A572M](#) for HSLA. For structural Grade 36, refer to Specification [A36/A36M](#).

1.2 *Units*—The values stated in inch-pound units are to be regarded as the standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.3 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.4 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 ASTM Standards:²

[A1 Specification for Carbon Steel Tee Rails](#)

¹ This specification is under the jurisdiction of ASTM Committee [A01](#) on Steel, Stainless Steel and Related Alloys and is the direct responsibility of Subcommittee [A01.15](#) on Bars.

Current edition approved Sept. 1, 2022. Published September 2022. Originally approved in 2012. Last previous edition approved in 2017 as A1075–12 (2017) ^{ϵ 1}. DOI: 10.1520/A1075-12R22.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

- [A6/A6M Specification for General Requirements for Rolled Structural Steel Bars, Plates, Shapes, and Sheet Piling](#)
- [A29/A29M Specification for General Requirements for Steel Bars, Carbon and Alloy, Hot-Wrought](#)
- [A36/A36M Specification for Carbon Structural Steel](#)
- [A123/A123M Specification for Zinc \(Hot-Dip Galvanized\) Coatings on Iron and Steel Products](#)
- [A370 Test Methods and Definitions for Mechanical Testing of Steel Products](#)
- [A499 Specification for Steel Bars and Shapes, Carbon Rolled from “T” Rails](#)
- [A572/A572M Specification for High-Strength Low-Alloy Columbium-Vanadium Structural Steel](#)
- 2.2 *AASHTO Standard:*
[AASHTO Manual for Assessing Safety Hardware](#)³

3. Terminology

3.1 *Definitions of Terms Specific to This Standard:*

3.1.1 *crashworthiness, n*—ability of signs, signals, and other safety hardware to fail in such a manner so as not to shatter or cause injury to passengers in vehicles involved in an impact or collision.

3.1.2 *lot, n*—for product produced from rolled “T” rails, a lot shall consist of material of the same size product produced in one shift in accordance with Specification [A499](#).

3.1.3 *U-channel post, n*—bars with a “flanged U shape” to provide increased stiffness when loaded in the transverse direction, typically having punched holes and primarily used for the attachment of highway signs.

4. Ordering Information

4.1 Orders for material under this specification should include the following information:

- 4.1.1 Quantity (weight or number of pieces);
- 4.1.2 Name of material (steel posts);
- 4.1.3 Grade of steel (Grades 50, 50LC, 60, 60LC, 70, or 80);
- 4.1.4 Weight per foot;
- 4.1.5 Condition (as-rolled, painted, powder coated, or galvanized);

³ Available from American Association of State Highway and Transportation Officials (AASHTO), 444 N. Capitol St., NW, Suite 249, Washington, DC 20001, <http://www.transportation.org>.