



Designation: E1481 – 00a (Reapproved 2021)

Standard Terminology of Railing Systems and Rails for Buildings¹

This standard is issued under the fixed designation E1481; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon (ϵ) indicates an editorial change since the last revision or reapproval.

1. Scope

1.1 This terminology consists of terms and definitions pertaining to railing systems and rails for buildings, and in particular, terms related to the standards generated by ASTM Committee E06 on Performance of Building Constructions.

1.2 The purpose of this terminology is to provide meanings and explanations of technical terms, written for both the technical expert and the non-expert user.

1.3 This terminology is one of a group of special terminologies subsidiary to the comprehensive Terminology **E631**.

1.4 Terms are listed in alphabetical sequence. Compound terms appear in the natural spoken order. Where definitions herein are adopted from other sources, they are exact copies. The source is identified at the right margin following the definition and is listed in Section 2.

1.5 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.6 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

2. Referenced Documents

2.1 *ASTM Standards:*²

E631 Terminology of Building Constructions

E935 Test Methods for Performance of Permanent Metal Railing Systems and Rails for Buildings

E985 Specification for Permanent Metal Railing Systems

and Rails for Buildings (Withdrawn 2015)³

2.2 *ANSI/ASSE Standard:*⁴

A1264.1 Safety Requirements for Workplace Floor and Wall Openings, Stairs, and Railing Systems

3. Terminology

3.1 *Definitions:*

baluster, baluster bar, *n*—one of a series of closely spaced, upright, and parallel infill members of a balustrade, located between top rail or handrail and bottom rail or tread or floor beneath balustrade. (Synonym for **picket**.)

baluster casting—an ornamental cast element attached to a baluster. Also, cast element designed to attach baluster to top and bottom rails.

baluster railing system—a system consisting of posts, balusters, top rail, and bottom rail.

balustrade, *n*—a railing system consisting of a row of balusters capped by a rail or handrail.

bottom rail—the lowest member of a railing system, supporting balusters or panels, if any.

building, *n*—a structure comprising a partially or totally enclosed space, erected by means of a planned process of forming and combining materials. **E631**

cap, *n*—a fitting or plug used to close the end of a pipe, tubular post, newel, or rail.

cap rail—a secondary railing element, often a handrail, fastened to the top rail of a railing system. (Synonym for *rail cap*.)

collar, *n*—Synonym for **escutcheon**. **E631**

cover flange—Synonym for **escutcheon**. **E631**

cover plate—Synonym for **escutcheon**.

cover ring—Synonym for **escutcheon**.

¹ This terminology is under the jurisdiction of ASTM Committee E06 on Performance of Buildings and is the direct responsibility of Subcommittee E06.56 on Performance of Railing Systems and Glass for Floors and Stairs.

Current edition approved Aug. 1, 2021. Published August 2021. Originally approved in 1992. Last previous edition approved in 2014 as E1481 – 00a (2014) ^{ϵ 1}. DOI: 10.1520/E1481-00AR21.

² For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

³ The last approved version of this historical standard is referenced on www.astm.org.

⁴ Available from American Society of Safety Engineers (ASSE), 520 N. Northwest Hwy., Park Ridge, IL 60068, <http://www.asse.org>.

- drop cap**—the cover of a railing post or newel that is exposed to view, usually below the stair stringer or floor. **E631**
- easement**, *n*—the curved portion of a rail and handrail forming a transition in the vertical plane between the horizontal and inclined sections of a handrail.
- escutcheon**, *n*—a protective or ornamental cover located at the termination of a post, baluster, or rail against a tread, floor, or wall. (Synonym for *collar*, *cover flange*, *cover plate*, or *cover ring*.)
- expanded metal*—See **screen**.
- finial**, *n*—an ornamental piece on the top of a post, newel, or railing; frequently in the form of an urn or pineapple, and so named. **E631**
- flange**, *n*—a flat plate or formed piece at the end of a railing or rail element for attachment to the adjoining construction or supporting member.
- grab bar*—Synonym for **grab rail**. **E631**
- grab rail**—a short length of rail located for safety or convenience to assist a person in movement at a specific location. (Synonym for *grab bar*.) **E631**
- guardrail system**—a railing system, providing protection for building users against accidental fall and injury, located at or near the outer edge of a stair, ramp, landing, platform, deck, balcony, hatchway, manhole, floor opening, porch, or accessible roof; at the perimeter of an opening or accessible surface, such as the opening of a stair; or at a location at which an operating condition requires access limitation to a designated area. (Compare **railing system**.)
- handgrip**, *n*—the part of a handrail designed to provide a secure grasp. **E631**
- handrail**, *n*—a horizontal, sloping, or vertical member normally grasped by hand for guidance or support.
DISCUSSION—This member may be part of a railing system and is often, but not necessarily, a top member (top rail), or may be mounted on a wall or other building element. When part of a stair-rail system, it is a member paralleling pitch of stair flight and is often, but not necessarily, a top member. (Compare **wall handrail**.)
- handrail bracket**—a device attached to a wall, post, or other surface to support the handrail. **E631**
- handrail height**—the vertical distance from the top surface of the top rail to the surface of the finished floor, top of a ramp, or the nosing line of stair treads. **E631**
- infill**, *n*—a series of balusters of a baluster railing system and the structural as well as the decorative elements, including the panels, mesh, or similar elements, of a panel railing system; located between top and bottom rails and posts; to serve the twofold purpose of (a) protecting bodies from penetrating and falling through the baluster and panel infill areas and (b) providing a specified resistance to horizontal thrusts as are potentially encountered within the infill area.
DISCUSSION—Infills should be designed in such a way as to deter climbing of the railing system.
- infill area**—the field of baluster and panel railing systems, bordered by top and bottom rails and posts. **E935**
- intermediate rail**—one of two or more rails between the top rail and floor.
- kick plate*—Synonym for **toe board**. **E631**
- lamb’s tongue**—an ornamental curved or tapered fitting terminating a handrail, usually tapered to the tip.
- lateral scroll**—a fitting that curves in a horizontal plane, used to terminate a handrail; often ending as a round plate covering the top of a post. **E631**
- mid rail**, *n*—a rail located between top rail and bottom rail or between top rail and floor if there is no bottom rail.
- miter ending**—an angular or dovetailed member end, designed to fit an adjacent matching member, thereby providing continuity of profile at the connection.
- newel**, *n*—a decorative or structural post member at the start or end of a stair run, often extending above a handrail; usually square or rectangular in cross section, supporting the end of a stair railing or serving as the common support for two stair railings, often supporting a stair stringer and platform; also, the center post of a spiral stair.
- ogee**, *n*—a molding with a profile having a double curve formed by a convex line turning into a concave line, resulting in an S-shape. **E631**
- panel**, *n*—a flat infill element between a top rail, bottom rail, and posts. **E631**
- picket**, *n*—Synonym for **baluster**, **baluster bar**.
- pineapple**, *n*—a finial in the form of a pineapple. **E631**
- pipe**, *n*—hollow round section of metal or other material, the size of which is usually designated by nominal size, in inches (millimetres), as influenced by inside diameter and wall thickness.
- pipe railing system**—a railing system fabricated of pipe or round tubing.
- post**, *n*—a vertical supporting member. **E631**
- queue-rail system*—Synonym for **traffic-rail system**.
- rail**, *n*—a horizontal, inclined, or vertical member of a railing system, such as top, intermediate, or bottom member connecting balusters or posts, or both, at specified intervals. (Compare **handrail**.) **E631, E985, A1264.1**
- rail cap*—Synonym for **cap rail**. **E631**
- railing*, *n*—Use **railing system**. **E631**
- railing return**—a bent at the end of a handrail, turning toward the wall or post to which the handrail is attached.
- railing system**—a framework of horizontal, inclined, vertical, and infill members, including panels and grillwork, for