



# Standard Test Method for Measuring Moment of Inertia and Center of Percussion of a Baseball or Softball Bat<sup>1</sup>

This standard is issued under the fixed designation F2398; the number immediately following the designation indicates the year of original adoption or, in the case of revision, the year of last revision. A number in parentheses indicates the year of last reapproval. A superscript epsilon ( $\epsilon$ ) indicates an editorial change since the last revision or reapproval.

## 1. Scope

1.1 Method for determining the moment of inertia (MOI), the center of percussion (COP), and the balance point (BP) of baseball and softball bats. These physical properties are used in Test Method F1881, Test Method F1890, and Test Methods F2219.

1.2 The MOI, COP, and BP are measured in the laboratory on test equipment meeting the requirements defined in this test method.

1.3 The values stated in inch-pound units are to be regarded as standard. The values given in parentheses are mathematical conversions to SI units that are provided for information only and are not considered standard.

1.4 *This standard does not purport to address all of the safety concerns, if any, associated with its use. It is the responsibility of the user of this standard to establish appropriate safety, health, and environmental practices and determine the applicability of regulatory limitations prior to use.*

1.5 *This international standard was developed in accordance with internationally recognized principles on standardization established in the Decision on Principles for the Development of International Standards, Guides and Recommendations issued by the World Trade Organization Technical Barriers to Trade (TBT) Committee.*

## 2. Referenced Documents

### 2.1 ASTM Standards:<sup>2</sup>

F1881 Test Method for Measuring Baseball Bat Performance Factor (Withdrawn 2014)<sup>3</sup>

F1890 Test Method for Measuring Softball and Baseball Bat Performance Factor

<sup>1</sup> This test method is under the jurisdiction of ASTM Committee F08 on Sports Equipment, Playing Surfaces, and Facilities and is the direct responsibility of Subcommittee F08.26 on Baseball and Softball Equipment.

Current edition approved July 1, 2020. Published August 2020. Originally approved in 2004. Last previous edition approved in 2015 as F2398 – 11 (2015). DOI: 10.1520/F2398-11R20.

<sup>2</sup> For referenced ASTM standards, visit the ASTM website, www.astm.org, or contact ASTM Customer Service at service@astm.org. For *Annual Book of ASTM Standards* volume information, refer to the standard's Document Summary page on the ASTM website.

<sup>3</sup> The last approved version of this historical standard is referenced on www.astm.org.

## F2219 Test Methods for Measuring High-Speed Bat Performance

## 3. Terminology

### 3.1 Definitions of Terms Specific to This Standard:

3.1.1 *balance point (BP), n*—the distance to the center of mass measured from the knob end of the bat.

3.1.2 *center of percussion (COP), n*—also known as the center of oscillation. Forces and impacts at this location will not induce reactions at the pivot point, 6 in. (152 mm) from the knob end of the bat.

3.1.3 *cycle, n*—one complete oscillation of a pendulum supported at the pivot point, 6 in. (152 mm) from the knob end of the bat.

3.1.4 *moment of inertia (MOI), n*—also known as the mass moment of inertia, the measure of the bat's resistance to changes in its rotation rate about the pivot point, 6 in. (152 mm) from the knob end of the bat.

3.1.5 *period, n*—the time required for a pendulum to oscillate through one complete cycle.

## 4. Significance and Use

4.1 This test method offers a laboratory means to measure the inertial properties of bats, specifically weight, balance point, center of percussion, and MOI, in support of other test methods including the ASTM standards referenced in this document.

4.2 Use of this test method can provide sports governing bodies the means to establish rules regarding the physical properties of bats, specifically MOI.

## 5. Apparatus

### 5.1 Bat MOI Test Apparatus:

5.1.1 *Ruler*, suitable for measuring lengths up to 42 in. (1067 mm) to the nearest 0.03 in. (0.8 mm).

5.1.2 *Weight Scales*, suitable for measuring weight up to 48 oz (1361 g) to the nearest 0.0035 oz (0.1 g).

5.1.3 *Electronic Timer*, suitable device sufficiently accurate for measuring time to the nearest 1  $\mu$ s (0.000001 s).

5.1.4 *Pendulum Stand*—A frame with a pivoting bat collar-clamp large enough to allow a bat held in a vertical position to swing freely (see Fig. 1).