This Research Report is issued under the fixed designation RR: D19-1160. You agree not to reproduce or circulate or quote, in whole or part, this document outside of ASTM International Committee/Society activities, or submit it to any other organization or standards body (whether national, international or other) except with the approval of the Chairman of the Committee having jurisdiction and the written authorization of the President of the Society. If you do not agree to these conditions, please immediately destroy all copies of this document. *Copyright ASTM International, 100 Barr Harbor Drive, West Conshohocken, PA 19428. All rights reserved.* 

27 December 1996

## Committee D19 on Water Subcommittee D19.03 on Sampling Water and Water-Formed Deposits, Analysis of Water for Power Generation and Process Use, On-Line Water Analysis, and Surveillance of Water

**Research Report D19-1160** 

Interlaboratory Study to Establish Precision Statements for ASTM D6071, Standard Test Method for Low Level Sodium in High Purity Water by Graphite Furnace Atomic Absorption Spectroscopy

> ASTM International 100 Barr Harbor Drive West Conshohocken, PA 19428-2959

1	INTRODUCTION
2	PARTICIPATING LABORATORIES
	2.1 Description
	2.2 List of Participants
3	SAMPLES
	3.1 Preparation and Shipment
	3.2 Sample Concentrations
4	ANALYTICAL METHODS
-	4.1 Selection of Methods for Validation
	4.2 Analytical Methods Used in the Study
	4.3 Method Availability
5	DATA ANALYSIS
v	DATA ANALYSIS
	5.2 Statistical Procedures
6	
a	METHOD PERFORMANCE 1   6.1 Summary Statistics 1
	Sodium by Graphite Furnace
	Sodium by Ion Chromatograph 1
	Potassium by Ion Chromatograph 1
	Calcium by Graphite Furnace 1
	Magnesium by Graphite Furnace 1
	Ammonia by Ion Chromatograph 1
	Chloride by Ion Chromatograph 1
	Fluoride by Ion Chromatograph 1
	Sulfate by Ion Chromatograph 1
	Phosphate by Ion Chromatograph 1
	Silica by Graphite Furnace 1
	Acetate by Ion Chromatograph 1
	Formate by Ion Chromatograph 1
	Total Organic Carbon
	6.2 Regression Coefficients, ug/L
	6.3 Derived Detection & Quantitation Limits 1
	6.4 Participant Estimates of LOD - Comparison 1
7	COMMENTS
8	SUMMARY
9	APPENDIX
-	

.

. . , t

## 1 INTRODUCTION

One important goal of RP2712-3 is to assure the validity of the measurements that are made on both continuous and grab samples taken from each of the six thermal plant systems to be studied. Those grab sample methods for which adequate performance information has not been available at the concentrations of interest to the project have been subjected to an interlaboratory validation program designed in accordance with ASTM D2777-85, "Standard Practice for Determination of the Precision and Bias of Applicable Methods of Committee D-19 on Water."

## 2 PARTICIPATING LABORATORIES

## 2.1 Description

Participants for the interlaboratory study were solicited from utility, vendor and consulting laboratories who were routinely using, or were qualified to use, one or more of the methods selected for the study. Samples were sent to twenty volunteer participants, some for all seven methods, others for only one or two. Un-anticipated laboratory work-load, personnel sickness or vacation conflicts, and instrument malfunctioning caused considerable attrition in the original list of volunteers to whom samples were sent. The following table lists those who submitted results for the indicated test methods.