Methods of test for

Self-locking nuts with maximum operating temperature greater than 425 °C

[ISO title: Aerospace — Self-locking nuts with maximum operating temperature greater than 425 $^{\circ}\text{C}$ — Test methods]

UDC 629.7.02:621.882.3:[621.882.54]:62 - 97:620.1

BSi

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Aerospace Standards Committee (ACE/-) to Technical Committee ACE/12 upon which the following bodies were represented:

Civil Aviation Authority (Airworthiness Division) Electronic Engineering Association Ministry of Defence Society of British Aerospace Companies Limited

This British Standard, having been prepared under the direction of the Aerospace Standards Committee, was published under the authority of the Board of BSI and comes into effect on 29 January 1988

© BSI 01-2000

relate to the work on this standard: Committee reference ACE/12 Draft for comment 85/72371 DC

The following BSI references

ISBN 0 580 16382 2

Amendments issued since publication

| Amd. No. | Date of issue | Comments |
|----------|---------------|----------|
| | | |
| | | |
| | | |
| | | |

Contents

| | Page |
|---|--------------------|
| Committees responsible | Inside front cover |
| National foreword | ii |
| Scope and field of application | 1 |
| 2 References | 1 |
| 3 Inspections and tests | 1 |
| Figure 1 | 2 |
| Figure 2 | 2 |
| Figure 3 | 3 |
| Figure 4 | 4 |
| Figure 5 | 5 |
| Figure 6 | 5 |
| Figure 7 | 5 |
| Figure 8 | 6 |
| Figure 9 | 8 |
| Figure 10 | 9 |
| Figure 11 | 11 |
| Figure 12 | 12 |
| Γable 1 — Bolt dimensions for self-locking torque test at | |
| ambient temperature (single cycle test) | 7 |
| Γable 2 — Test bolt coating in relation to the coating of the | _ |
| nut to be tested | 7 |
| Table 3 — Dimensions of the mandrels for permanent set test | 10 |
| Publications referred to | Inside back cover |