



## BSI Standards Publication

**Aerospace series - Nuts, anchor, self-locking, fuel resistant, sealing, floating, two lug, with counterbore, in alloy steel, cadmium plated, MoS2 lubricated - Classification: 900 MPa (at ambient temperature) / 120 °C**

---

## National foreword

This British Standard is the UK implementation of EN 2880:2018, incorporating corrigenda January and April 2019.

The start and finish of text introduced or altered by corrigendum is indicated in the text by tags. Text altered by CEN corrigendum April 2019 is indicated in the text by AC AC.

The UK participation in its preparation was entrusted to Technical Committee ACE/12, Aerospace fasteners and fastening systems.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019  
Published by BSI Standards Limited 2019

ISBN 978 0 539 04604 5

ICS 49.030.30

**Compliance with a British Standard cannot confer immunity from legal obligations.**

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 September 2018.

### Amendments/corrigenda issued since publication

Date	Text affected
31 January 2019	Implementation of CEN correction notice 18 December 2018: supersession details added to CEN title page
30 April 2019	Implementation of CEN corrigendum April 2019

ICS 49.030.30

English Version

**Aerospace series - Nuts, anchor, self-locking,  
fuel resistant, sealing, floating, two lug, with  
counterbore, in alloy steel, cadmium plated, Mo2  
lubricated - Classification: 900 MPa (at ambient  
temperature) / 120 °C**

Série aérospatiale - Écrous à river, à freinage interne, étanches au carburant, flottants, double patte, avec chambrage, en acier allié, cadmiés, lubrifiés MoS2 - Classification: 900 MPa (à température ambiante) / 120 °C

Luft- und Raumfahrt - Anniemuttern, selbstsichernd, druckdicht, kraftstoffbeständig, beweglich, beiderseitiger Flansch, mit zylindrischer Aussenkung, aus legiertem Stahl, verkadmet, MoS2-geschmiert - Klasse: 900 MPa (bei Raumtemperatur) / 120 °C

This European Standard was approved by CEN on 11 June 2018.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION  
COMITÉ EUROPÉEN DE NORMALISATION  
EUROPÄISCHES KOMITEE FÜR NORMUNG

**CEN-CENELEC Management Centre: Avenue Marnix 17, B-1000 Brussels**