



BSI Standards Publication

Aerospace series – Cables, electrical, for general purpose, single and multicore assembly – XLETFE Family – Jacketed or screened and jacketed

Part 011: Nickel plated copper – Operating temperatures, between – 65 °C and 150 °C – Dual extruded wall for open applications, with jacket without screen – UV laser printable – Product standard

National foreword

This British Standard is the UK implementation of EN 4612-011:2019. It supersedes BS EN 4612-011:2011, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee ACE/6, Aerospace avionic electrical and fibre optic technology.

A list of organizations represented on this committee can be obtained on request to its secretary.

This publication does not purport to include all the necessary provisions of a contract. Users are responsible for its correct application.

© The British Standards Institution 2019
Published by BSI Standards Limited 2019

ISBN 978 0 539 07004 0

ICS 49.060

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 30 September 2019.

Amendments/corrigenda issued since publication

Date	Text affected
31 October 2019	Implementation of CEN correction notice 15 October 2019: Figure in Clause 7 corrected

EUROPEAN STANDARD

EN 4612-011

NORME EUROPÉENNE

EUROPÄISCHE NORM

August 2019

ICS 49.060

Supersedes EN 4612-011:2011

English Version

Aerospace series - Cables, electrical, for general purpose, single and multicore assembly - XLETFE Family - Jacketed or screened and jacketed - Part 011: Nickel plated copper - Operating temperatures, between - 65 °C and 150 °C - Dual extruded wall for open applications, with jacket without screen - UV laser printable - Product standard

Série aérospatiale - Câbles, électriques, d'usage général, mono et multiconducteurs - Famille XLETFE - Gainés ou blindés et gainés - Partie 011 : Cuivre nickelé - Températures de fonctionnement comprises entre - 65 °C et 150 °C - Fil double isolé pour applications externes, gainé et non blindé - Marquable au laser UV - Norme de produit

Luft- und Raumfahrt - Ein- und mehradrige elektrische Leitungen für allgemeine Verwendung - XLETFE Familie - mit Mantel oder geschirmt und Mantel - Teil 011: Kupfer vernickelt - Betriebstemperaturen zwischen - 65 °C und 150 °C - Doppelt extrudierte Isolierung für externe Verwendung, mit Mantel ohne Schirm (Geflecht) - UV-Laser bedruckbar - Produktnorm

This European Standard was approved by CEN on 5 May 2019.

This European Standard was corrected and reissued by the CEN-CENELEC Management Centre on 16 October 2019.

CEN members are bound to comply with the CEN/CENELEC Internal Regulations which stipulate the conditions for giving this European Standard the status of a national standard without any alteration. Up-to-date lists and bibliographical references concerning such national standards may be obtained on application to the CEN-CENELEC Management Centre or to any CEN member.

This European Standard exists in three official versions (English, French, German). A version in any other language made by translation under the responsibility of a CEN member into its own language and notified to the CEN-CENELEC Management Centre has the same status as the official versions.

CEN members are the national standards bodies of Austria, Belgium, Bulgaria, Croatia, Cyprus, Czech Republic, Denmark, Estonia, Finland, France, Germany, Greece, Hungary, Iceland, Ireland, Italy, Latvia, Lithuania, Luxembourg, Malta, Netherlands, Norway, Poland, Portugal, Republic of North Macedonia, Romania, Serbia, Slovakia, Slovenia, Spain, Sweden, Switzerland, Turkey and United Kingdom.



EUROPEAN COMMITTEE FOR STANDARDIZATION
COMITÉ EUROPÉEN DE NORMALISATION
EUROPÄISCHES KOMITEE FÜR NORMUNG

CEN-CENELEC Management Centre: Rue de la Science 23, B-1040 Brussels