BS 2G 238: 1996

**Specification for** 

Electric cables for general airframe or equipment interconnect use (260 °C), nickel plated copper and copper alloy conductors, with wrapped insulation



NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

## Committees responsible for this **British Standard**

The preparation of this British Standard was entrusted to Technical Committee ACE/6, Aerospace avionic electrical and fibre optic technology, upon which the following bodies were represented:

British Airways British Cable Makers' Confederation British Rubber Manufacturers' Association Civil Aviation Authority (Airworthiness Division) Federation of the Electronics Industry Ministry of Defence Society of British Aerospace Companies Ltd.

This British Standard, having been prepared under the direction of the Engineering Sector Board, was published under the authority of the Standards Board and comes into effect on 15 January 1996

© BSI 09-1999

## Amendments issued since publication

First published September 1987 Second edition January 1996	Amd. No.	Date	Comments
The following BSI references relate to the work on this			
standard: Committee reference ACE/6 Draft for comment 93/708471 DC			
ISBN 0 580 24798 8			

## Contents

	Page	
Committees responsible	Inside front cover	
Foreword	ii	
1 Scope	1	
2 References	1	
3 Definitions	1	
4 Classification	1	
5 Construction	1	
6 Designation and marking	2	
7 Packaging and labelling	2	
8 Tests	2	
9 Reference samples	3	
Annex A (normative) Continuous current ratings	15	
Figure A.1 — Variation of resistance of copper with temperature	ature 16	
Table 1 — Type 01, class 1: single-core interconnect cables (	260 °C) 3	
Table 2 — Type 02, class 1: single-core unscreened airframe		
cables (260 °C)		
Table 3 — Type 01, classes 2, 3 and 4: multi-core unscreened,		
twisted interconnect cables without jacket (260 $^{\circ}\mathrm{C}$ )		
Table 4 — Type 02, classes 2, 3, and 4: multi-core unscreened, twisted airframe cables without jacket (260 °C)		
Table 5 — Type 03, classes 2, 3 and 4: multi-core unscreened,		
twisted interconnect cables with jacket (260°C)	4	
Table 6 — Type 04, classes 2, 3 and 4: multi-core unscreened, twisted interconnect cables with incket (260 $^{\circ}$ C)		
Table 7 — Type 05 classes 1 $2$ 3 and 4: single-core screened	o d	
with jacket and multi-core twisted and screened with jacket	,	
interconnect cable (260 °C)		
Table 8 — Type 06, classes 1, 2, 3 and 4: single-core screene	d	
with jacket, and multi-core twisted and screened with		
jacket, airframe cables (260 °C)	6	
Table 9 — Tensile strength and elongation at break of copper		
and copper alloy conductors		
Table 10 — Tests and requirements for cables types 01 and 02		
Table 11 — Tests and requirements for cables types 05 and 06		
Table 12 — Test application		
Table 13 — Specific test parameters		
Table A.1 — Continuous current ratings	15	
List of references Inside bac		