

### **BSI Standards Publication**

Hydraulic fluid power — Mounting dimensions for accessories for single rod cylinders, 16 MPa (160 bar) medium and 25 MPa (250 bar) series



BS ISO 8132:2022 BRITISH STANDARD

#### National foreword

This British Standard is the UK implementation of <u>ISO 8132:2022</u>. It supersedes <u>BS ISO 8132:2014</u>, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee MCE/18/-/3, Cylinders.

A list of organizations represented on this committee can be obtained on request to its committee manager.

#### **Contractual and legal considerations**

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2022 Published by BSI Standards Limited 2022

ISBN 978 0 539 14469 7

ICS 23.100.20

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 August 2022.

#### Amendments/corrigenda issued since publication

Date Text affected

BS ISO 8132:2022

## INTERNATIONAL STANDARD

ISO 8132

Fourth edition 2022-04-27

# Hydraulic fluid power — Mounting dimensions for accessories for single rod cylinders, 16 MPa (160 bar) medium and 25 MPa (250 bar) series

Transmissions hydrauliques — Dimensions d'interchangeabilité des accessoires pour vérins à simple tige, 16 MPa (160 bar) série moyenne et 25 MPa (250 bar)

