

BSI Standards Publication

Connections for hydraulic fluid power and general use — Hose fittings

Part 2: Hose fittings with ISO 8434-1 24° cone connector ends with O-rings



BS ISO 12151-2:2022 BRITISH STANDARD

National foreword

This British Standard is the UK implementation of <u>ISO 12151-2:2022</u>. It supersedes <u>BS ISO 12151-2:2003</u>, which is withdrawn.

The UK participation in its preparation was entrusted to Technical Committee MCE/18/-/4, Connectors and associated components.

A list of organizations represented on this committee can be obtained on request to its committee manager.

Contractual and legal considerations

This publication has been prepared in good faith, however no representation, warranty, assurance or undertaking (express or implied) is or will be made, and no responsibility or liability is or will be accepted by BSI in relation to the adequacy, accuracy, completeness or reasonableness of this publication. All and any such responsibility and liability is expressly disclaimed to the full extent permitted by the law.

This publication is provided as is, and is to be used at the recipient's own risk.

The recipient is advised to consider seeking professional guidance with respect to its use of this publication.

This publication is not intended to constitute a contract. Users are responsible for its correct application.

© The British Standards Institution 2022 Published by BSI Standards Limited 2022

ISBN 978 0 539 16943 0

ICS 23.040.70; 23.100.40

Compliance with a British Standard cannot confer immunity from legal obligations.

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 31 October 2022.

Amendments/corrigenda issued since publication

Date Text affected

BS ISO 12151-2:2022

INTERNATIONAL STANDARD

ISO 12151-2

Second edition 2022-10-14

Connections for hydraulic fluid power and general use — Hose fittings —

Part 2:

Hose fittings with ISO 8434-1 24° cone connector ends with O-rings

Raccordements pour transmissions hydrauliques et applications générales — Flexibles de raccordement —

Partie 2: Flexibles avec embouts à cône à 24 degrés et joints toriques conformes à l'ISO 8434-1

