

**BRITISH STANDARD**

# **Specification for gauge blanks**

## **Part 1: Plug, ring and calliper gauges**

ICS 17.040.30

### **Publishing and copyright information**

The BSI copyright notice displayed in this document indicates when the document was last issued.

© BSI 2009

ISBN 978 0 580 68742 6

The following BSI references relate to the work on this standard:

Committee reference TDW/4

Draft for comment 08/30177726 DC

### **Publication history**

First published 1942

Second edition, June 1964

Third edition, November 2008

### **Amendments issued since publication**

<b>Amd. no.</b>	<b>Date</b>	<b>Text affected</b>
C1	October 2009	See foreword

# Contents

Foreword *iv*

**1** Scope *1*

Section 1: General *2*

**2** Removal of sharp edges *2*

**3** Centres *2*

**4** Stabilization *2*

Section 2: Plain and screw plug gauges renewable end types *3*

**5** Gauging members and handles *3*

**6** Plain plug gauging members *24*

**7** Screw plug gauging members *29*

**8** Plug gauges other than cylindrical *37*

Section 3: Plain and screw ring gauges and plain gap gauges, solid types *40*

**9** Plain ring gauges *40*

**10** Screw ring gauges *40*

**11** Plain gap gauges, solid type *45*

Section 4: Adjustable screw ring gauges *47*

**12** General *47*

**13** Dimensions for adjustable screw ring gauge blanks for parallel threads *48*

## Annexes

Annex A (informative) Types of gauges *57*

Annex B (informative) Recommendations for adjustable calliper gauges *60*

Bibliography *62*

## List of figures

Figure 1 – Protected centre *2*

Figure 2 – Collet type plain plug gauges (Range: above 0.015 in up to and including 0.760 in) *4*

Figure 3 – Collet type screw plug gauges (Range: above 0.030 in up to and including 0.760 in) *5*

Figure 4 – Taper lock plug gauges *15*

Figure 5 – Trilock plain cylindrical plug gauges (Range: above 1.510 in up to and including 2.510 in) *17*

Figure 6 – Trilock screw plug gauges (Range: above 1.510 in up to and including 2.510 in) *18*

Figure 7 – Trilock plain cylindrical plug gauges (Range: above 2.510 in up to and including 8.010 in) *19*

Figure 8 – Trilock screw plug gauges (Range: above 2.510 in up to and including 8.010 in) *20*

Figure 9 – Annular design ball handle type plug gauges (Range: above 8.010 in up to and including 12.010 in) *22*

Figure 10 – Annular plug gauges – Bar handle types *23*

Figure 11 – Ball handles *28*

Figure 12 – Example of built-up gap gauge *46*

Figure 13 – Adjustable screw ring gauge, showing details of construction *47*

Figure 14 – Range: 0.059 in up to and including 0.150 in *48*