

CONFIRMED
DECEMBER 2007

Float operated valves —

**Part 3: Specification for diaphragm
type float operated valves (plastics
bodied) for cold water services only
(excluding floats)**



Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Building Services Standards Policy Committee (SEB/-) to Technical Committee SEB/2, upon which the following bodies were represented:

Association of Manufacturers of Domestic Electrical Appliances
 Association of Manufacturers of Domestic Unvented Supply Systems Equipment (MODUSSE)
 Association of Water Officers Ltd.
 British Bathroom Council
 British Gas plc
 British Non-Ferrous Metals Federation
 British Plastics Federation
 British Plumbing Fittings Manufacturers' Association
 British Valve and Actuator Manufacturers' Association
 Builders Merchants' Federation
 Consumer Policy Committee of BSI
 Department of the Environment (Building Research Establishment)
 Department of the Environment (Property Services Agency)
 Department of the Environment (Water Directorate)
 Department of Trade and Industry (National Weights and Measures Laboratory)
 Institute of Clerks of Works of Great Britain Inc.
 Institute of Plumbing
 Institution of Gas Engineers
 Institution of Water and Environmental Management
 Metal Sink Manufacturers' Association
 National Association of Plumbing, Heating and Mechanical Services Contractors
 Royal Institute of British Architects
 Society of British Gas Industries
 South London Consortium
 Water Companies Association
 Water Services Association of England and Wales

This British Standard, having been prepared under the direction of the Building Services Standards Policy Committee, was published under the authority of the Board of BSI and comes into effect on 31 December 1990

© BSI 04-1999

First published July 1979
 Second edition December 1990

The following BSI references relate to the work on this standard:
 Committee reference SEB/2
 Draft for comment 88/14227 DC

ISBN 0 580 18969 4

Amendments issued since publication

Amd. No.	Date	Comments

Contents

	Page
Committees responsible	Inside front cover
Foreword	ii
<hr/>	
Section 1. General	
1 Scope	1
2 Definitions	1
3 Designation for ordering	1
4 Marking	1
<hr/>	
Section 2. Materials	
5 Effect of non-metallic materials on water quality	4
6 Plastics	4
7 Metals	4
<hr/>	
Section 3. Design, construction and dimensions	
8 Inlet connection	5
9 Seats	6
10 Backnuts	6
11 Float arm or float arm assembly	6
12 Discharge arrangement	6
<hr/>	
Section 4. Performance	
13 Distortion and deflection	8
14 Hydraulic pressure	8
15 Backflow prevention	8
16 Flow	8
17 Endurance	8
<hr/>	
Appendix A Distortion test for backnuts and inlet shank	9
Appendix B Diaphragm type float operated valve assembly test	9
Appendix C Float attachment thread distortion test	12
Appendix D Shut-off pressure test	12
Appendix E Method of test for effect of dynamic pressure on discharge arrangement	13
Appendix F Backflow prevention test	13
Appendix G Flow test	14
Appendix H Endurance test	16
<hr/>	
Figure 1 — Illustration of effective warning water level in relation to other commonly defined levels in a British Standard flushing cistern	2
Figure 2 — Bottom entry valve inlet arrangement	3
Figure 3 — Side inlet shank connectors	5
Figure 4 — Hexagonal backnuts	6
Figure 5 — Float connecting dimensions	7
Figure 6 — Inlet shank and backnuts test plate	9
Figure 7 — Valve assembly deflection test	10
Figure 8 — Float attachment thread distortion test piece	12
Figure 9 — Typical arrangement of apparatus for backflow prevention test	14
Figure 10 — Flow test apparatus	15
<hr/>	
Publications referred to	Inside back cover