



BSI Standards Publication

**Limits and fits – Guidance  
for system of cone (taper)  
fits and tolerances for cones  
from  $C = 1:3$  to  $1:500$ , lengths  
from 6 mm to 630 mm and  
diameters up to 500 mm**

### **Publishing and copyright information**

The BSI copyright notice displayed in this document indicates when the document was last issued.

© BSI 2009

ISBN 978 0 580 65211 0

ICS 17.040.10

The following BSI references relate to the work on this standard:

Committee reference TDW/4

Draft for comment 09/30192596 DC

### **Publication history**

BS 4500-4 first published November 1985

BS 4500-5 first published November 1988

First published as BS 4500 September 2009

### **Amendments issued since publication**

<b>Date</b>	<b>Text affected</b>
-------------	----------------------

---

# Contents

Foreword *iii*

## Section 1: General 1

- 1 Scope 1
- 2 Normative references 1
- 3 Terms and definitions 1

## Section 2: System of cone fits 15

- 4 Formation of cone fits 15
- 5 Calculation of axial displacements for the hole basis system of cone fits 18

## Section 3: System of cone tolerances 27

- 6 Basis of the system 27
- 7 Cone diameter tolerance ( $T_D$ ) 28
- 8 Cone angle tolerance ( $AT$ ) 28
- 9 Cone form tolerances ( $T_F$ ) 29
- 10 Cone section diameter tolerance ( $T_{DS}$ ) 29
- 11 Table of cone angle tolerances – structure of the table 29

## Annexes

Annex A (informative) Effect on the cone fit of departures of the internal and external cones from the basic cone 33

Annex B (informative) Maximum cone angle deviations resulting from the cone diameter tolerances ( $T_D$ ) for 100 mm cone length 39

Bibliography 41

## List of figures

Figure 1 – Actual cone 7

Figure 2 – Basic cone 8

Figure 3 – Cone 8

Figure 4 – Conical workpiece – external cone 8

Figure 5 – Conical workpiece – internal cone 9

Figure 6 – General definitions 9

Figure 7 – Limit cones, cone diameter, tolerance zone and straightness of the generator tolerance zone 10

Figure 8 – Angles on cones 10

Figure 9 – Limit cone angles 11

Figure 10 – Maximum and minimum interference of a cone interference fit made by a defined axial displacement of the cones with respect to each other from the actual starting position  $P_a$  (pressing in and on respectively by displacement  $E_{amin}$  and  $E_{amax}$  respectively) 11

Figure 11 – Limit starting positions 12

Figure 12 – Admissible limit cone angles resulting from the cone diameter tolerance 12

Figure 13 – Cone diameter tolerance zone and roundness tolerance zone 13

Figure 14 – Cone section diameter tolerance ( $T_{DS}$ ) and cone angle tolerance ( $AT$ ) 13

Figure 15 – Actual cone angles 14

Figure 16 – Position of the cone angle within the cone diameter tolerance zone 14

Figure 17 – Cone clearance fit made by constructional formation (final position  $P_f$  fixed by contact at a collar) 16

Figure 18 – Cone interference fit made by pressing in to a defined dimension (final position  $P_f$  fixed by distance  $a$ ) 16