Fire extinguishing installations and equipment on premises —

Part 4: Specification for carbon dioxide systems

 $ICS \ 13.220.20$



NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

Committees responsible for this British Standard

The preparation of this British Standard was entrusted to Technical Committee FSH/18, upon which the following bodies were represented:

British Fire Protection Systems Association Chief and Assistant Chief Fire Officers Association Health and Safety Executive Home Office Institute of Fire Safety Institution of Fire Engineers London Fire and Civil Defence Authority Loss Prevention Council Maritime and Coastguard Agency Ministry of Defence Society of Motor Manufacturers and Traders Warrington Fire Research Centre

This British Standard, having been prepared under the direction of the Health and Environment Sector Committee, was published under the authority of the Standards Committee and comes into effect on

15 August 2001

© The British Standards Institution 2012 Published by BSI Standards Limited 2012

First published October 1979 Second edition March 1986 Third edition August 2001

The following BSI references relate to the work on this standard:

Committee reference FSH/18 Draft for comment 00/541249 DC; 11/30244843 DC

ISBN 978 0 580 75095 3

Amendments issued since publication

	Amd. No.	Date	Comments
	A1	April 2012	See Foreword for details
С;			

Contents

		Page		
Forev	word	iii		
Introduction				
1	Scope	1		
2	Normative references	1		
3	Terms and definitions	4		
4	Characteristics and uses of carbon dioxide	5		
5	Types of system	6		
6	Planning	7		
7	Specifications, plans and approvals	7		
8	Commissioning and acceptance	8		
9	Inspection, maintenance, testing and training	11		
10	Total flooding systems	12		
11	Local application systems	22		
12	Manual hose systems	28		
13	System components	29		
14	System operation	30		
15	Safety precautions	30		
16	Carbon dioxide supply	36		
17	Quantity of carbon dioxide	36		
18	Storage containers	36		
19	Pipework	38		
20	Installation of pipework	42		
21	Marking of pipework	45		
Anne	x A (normative) Door fan test for determination of minimum hold time	46		
Annex B (informative) Service schedule				
Annex C (normative) Determination of carbon dioxide concentrations for flammable liquids and gases				
Annex D (informative) Examples of calculation of carbon dioxide				
requirements				
Annex E (informative) Determination of carbon dioxide pipe and orifice size				
Bibliography				
Figur withi	re 1 — Calculated CO_2 loss rate based on an assumed 21 °C temperature n the enclosure and 21 °C ambient outside	15		
Figur	re 1a — Discharge rates versus perimeter enclosed	26		
Figure 2 — Aiming position for angled discharge nozzles				
Figur	re 3 — Label to be displayed at manual control	34		
Figur	re 4 — Label to be displayed at entrances to hazard	35		
Figur	re C.1 — Cup burner apparatus	57		
Figure D.1 — Example printer with a large enclosure				
Figure D.2 — Example paint spray booth, open front and open top				
Figure D.3 — Example paint spray booth, open front, one open side and open top				
Figur	e E.1 — Pressure drop in pipeline for 20.7 bar storage pressure	66		
Figur	re $E.2$ — Pressure drop in pipeline for 51.7 bar storage pressure	67		
Table 0 — Physical properties of carbon dioxide 6				
Table 1 — Volume factors				
Table	2 - Minimum carbon dioxide concentration for extinction	18		
Table	e 3 — Design concentrations and flooding factors for specific hazards	19		