# Concrete pipes and ancillary concrete products —

Part 5: Specification for prestressed non-pressure pipes and fittings with flexible joints

 $ICS \ 23.040.50$ 



NO COPYING WITHOUT BSI PERMISSION EXCEPT AS PERMITTED BY COPYRIGHT LAW

## Committees responsible for this **British Standard**

The preparation of this British Standard was entrusted to Committee B/505, Wastewater engineering, upon which the following bodies were represented:

**British Plastics Federation** British Water CMF — Cast Metals Federation Chartered Institution of Water and Environmental Management Clay Pipe Development Association Ltd. CPSA — Concrete Pipeline Systems Association Institute of Cast Metal Engineers Institute of Civil Engineers Institute of Plumbing LOTAG — London Technical Advisors Group ODPM (represented by Waterman Burrow Crock) Society of British Water Industries Water UK

This British Standard was published under the authority of the Standards Policy and Strategy Committee and comes into effect on 31 October 2004

© BSI 2010

#### Amd. No. Date Comments June 2010 See Foreword A1The following BSI references relate to the work on this British Standard: Committee reference B/505 Draft for comment 99/109528 DC 09/30209267 DC ISBN 978 0 580 69021 1

### Amendments/corrigenda issued since publication

## Contents

	Ι	Page	
Committees responsible Inside front correvord		cover	
		ii	
1	Scope	1	
2	Normative references	1	
3	Terms and definitions	2	
4	Symbols	4	
<b>5</b>	General requirements	4	
6	Special requirements	9	
7	Conformity evaluation	11	
8	Marking	12	
Ann	ex A (informative) Information to be supplied in an enquiry or order	13	
Ann	ex B (informative) British Standards relevant to BS EN 1916:2002	13	
Ann	ex C (normative) Supplementary provisions for prestressing wire	14	
Annex D (nornative) Surface finish tests		20	
Ann	ex E (normative) Dimensional tests	22	
Bibliography		25	
Figu	re 1 — Typical section of a prestressed concrete pipe with a spigot		
and	socket joint	2	
Figu	re 2 — Typical splay pipes	3	
Figu	re C.1 — A test cylinder and its accessories	16	
Figu	are $C.2$ — Test tank and arrangement of a test cylinder in acid solution	17	
Figu	re C.3 — A wire-wrapped test cylinder	19	
Figu	re C.4 — Typical arrangement for winding a test cylinder	20	
Figu	ure D.1 — Gauge for assessing surface eveness	20	
Figu	ure D.2 — Gauge for assessing surface voids	21	
Figu	re E.1 — Gauge for measuring deviation from internal straightness	23	
Tabl	le 1 — Symbols	4	
Tabl whe	le 2 — Limiting values of composition and properties for concrete re a DC-class is specified	5	
Tabl	le 3 — General purpose cements and combinations	6	
Tabl tole	le 4 — Nominal sizes, internal manufacturing diameters and rances of units	8	
Tab	le 5 — Minimum crushing loads for strength class 120 units	9	
Tabl	le B.1 — British Standards relevant to BS EN 1916:2002	13	