

Code of practice for

**Ventilation principles  
and designing for  
natural ventilation**

# Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the Basic Data and Performance Criteria for Civil Engineering and Building Structures Standards Policy Committee (BDB/-) to Technical Committee BDB/2, upon which the following bodies were represented:

Aggregate Concrete Block Association	Department of the Environment (Construction Industries Directorate)
Association for the Conservation of Energy	Department of the Environment for Northern Ireland
Association of Building Component Manufacturers	Electricity Supply Industry in United Kingdom
Association of County Councils	Eurisol (UK Mineral Wool Association)
Association of District Councils	Flat Glass Manufacturers' Association
Association of Metropolitan Authorities	Gypsum Products Development Association
Autoclaved Aerated Concrete Products Association	Hevac Association
Brick Development Association	Institution of Civil Engineers
British Board of Agrément	Institution of Gas Engineers
British Cement Association	Institution of Structural Engineers
British Gas plc	Lighting Industry Federation Ltd.
British Precast Concrete Federation Ltd.	Ministry of Defence
Building Employers' Confederation	National House-building Council
Building Services Research and Information Association	National Illumination Committee of Great Britain
Chartered Institute of Building	Royal Institute of British Architects
Chartered Institution of Building Services Engineers	Royal Institution of Chartered Surveyors
Concrete Society	Scottish Development Department
Consumer Policy Committee of BSI	Society of Chief Architects of Local Authorities
Cranfield Institute of Technology	Timber Research and Development Association
Department of Education and Science	Trades Union Congress
Department of Energy (Energy Efficiency Office)	Watt Committee on Energy Ltd.
Department of Health	
Department of the Environment (Building Research Establishment)	

The following bodies were also represented in the drafting of the standard, through subcommittees and panels:

Association of Lightweight Aggregate Manufacturers	Institution of Mechanical Engineers
British Coal Corporation	Medical Research Council
British Concrete Masonry Association	National Council of Building Material Producers
Flat Roofing Contractors Advisory Board	Phenolic Foam Manufacturers' Association

This British Standard, having been prepared under the direction of the Basic Data and Performance Criteria for Civil Engineering and Building Structures Standards Policy Committee, was published under the authority of the Standards Board and comes into effect on 31 May 1991

© BSI 01-2000

First published September 1980  
Second edition May 1991

The following BSI references relate to the work on this standard:  
Committee reference BDB/2  
Draft for comment 89/17211 DC

ISBN 0 580 19285 7

## Amendments issued since publication

Amd. No.	Date	Comments
8930	December 1995	Indicated by a sideline in the margin

# Contents

	Page
Committees responsible	Inside front cover
Foreword	ii
<hr/>	
Section 1. General	
1 Scope	1
2 Definitions	1
3 Symbols	2
<hr/>	
Section 2. General principles of ventilation	
4 Basic data	3
5 Application	9
6 Provision for ventilation	9
7 Choice between natural and mechanical ventilation	13
<hr/>	
Section 3. Natural ventilation	
8 General	15
9 Flow characteristics of openings	15
10 Generation of pressure differences	16
11 Meteorological variables	18
12 Determination of natural ventilation rates	19
13 Other mechanisms of natural ventilation	23
14 Fire ventilation	25
15 Air infiltration	25
16 Normal building practice for natural ventilation in dwellings	26
<hr/>	
Appendix A Bibliography	28
Appendix B Calculation of contaminant concentration	29
Appendix C Calculation of ventilation rates to reduce the risk of surface condensation under steady state conditions	33
Appendix D Determination of ventilation requirements	34
Appendix E Calculation of reference wind speed $u_r$	35
Appendix F Calculation of natural ventilation rates for a simple building	36
<hr/>	
Index	39
<hr/>	
Figure 1 — Ventilation required to reduce the risk of surface condensation occurring on the inner wall surface for various wall $U$ -values and ambient air conditions	6
Figure 2 — Typical possibilities for inlets and outlets, for both natural and mechanical ventilation systems in dwellings	12
Figure 3 — Correction to the dry resultant temperature to take account of air movement	13
Figure 4 — Pressure difference and flow created by temperature difference	18
Figure 5 — Contours of $u_{50}$ for the UK	20
Figure 6 — Arrangement of openings in a simple building	23
Figure 7 — Variation of $J(\phi)$ with angle opening $\phi$ for (a) side-mounted casement windows and (b) centre-pivoted windows	26
Figure 8 — Variation of gas concentration $c$ with $t$ and ventilation rate $Q$ for gas leakage rate $q$	30
Figure 9 — Allowable reduction in minimum fresh air supply rate when the pollutant source is present for a limited period, $t_1$ , rather than continuously	31