Incorporating Corrigendum No. 1

Assessment of inadvertent initiation of bridge wire electro-explosive devices by radio-frequency radiation — Guide

 $ICS\ 13.280$



Committees responsible for this British Standard

The preparation of this British Standard was entrusted to Technical Committee GEL/602, upon which the following bodies were represented:

BBC — British Broadcasting Corporation

BEAMA Ltd. — GAMBICA

Chamber of Shipping

Engineering Equipment and Materials Users Association

ERA Technology Ltd

HSE — Health and Safety Executive

Institute of Petroleum

Institution of Gas Engineers

Ministry of Defence — UK Defence Standardization

Radio Society of Great Britain

SIRA Limited

UK Offshore Operators Association Limited

Co-opted member

This British Standard, having been prepared under the direction of the Electrotechnical Sector Policy and Strategy Committee, was published under the authority of the Standards Policy and Strategy Committee on 30 October 2002

© BSI 30 June 2003

First published February 1986 First revision November 1991 Second revision October 2002

The following BSI references relate to the work on this British Standard: Committee reference GEL/602

ISBN 0 580 40351 3

Amendments issued since publication

Date	Amd No.	Comments
14499 Corrigendum No. 1		Changes to Figure 15

Contents

		Page
Com	mittees responsible Inside front of	cover
Fore	word	iii
Intro	oduction	1
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols and abbreviations	3
5	General considerations	4
6	Transmitters and transmitter output parameters	5
7	Circuits for blasting and well perforation	7
8	Electro-explosive devices	13
9	Methods of assessment for determining potential RF ignition hazards on a site where EED are used	15
10	Practical on-site testing	61
11	Safety procedures	62
12	Special applications	62
Anne	ex A (informative) Extraction of energy from the electromagnetic field	64
Anne	ex B (informative) Measurement of electromagnetic fields	64
Anne bodie	ex C (informative) Sources of information and addresses of advisory	67
	ex D (informative) Electromagnetic radiated fields and examples of ating antennas and unintended receiving antenna characteristics	69
Anne an E	ex E (informative) The effective resistance of the leading wires of EED	76
	ex F (informative) Derivation of minimum distances of safe approach fo e 2 and Table 3	or 80
Annex G (informative) Ground-wave propagation (vertical polarization): calculation of field strength		81
	ex H (informative) Worked examples to demonstrate the effects of nna gain	83
the ι	ex I (informative) The effects of leading wire resistance, safety resistors use of EED with different characteristics	83
	ex J (informative) Derivation of Figure 12a) to Figure 12g) for EED alor porating the resistance of leading wires and safety resistances	ne 85
Bibli	iography	87
Figu	re 1 — Typical single extended line blasting circuits (plan view)	8
Figu	re 2 — Typical multiple extended line blasting circuits (plan view)	8
Figu	re 3 — Quarry blast including toe shots	9
Figu	re 4 — Multilevel series-in-parallel demolition blast	10
Figu	m re~5-Layout~of~wireline~cable~for~offshore~and~land~based~operations	11
Figu	re 6 — Section through a typical commercial instantaneous EED	13
Figu	re 7 — Flow diagram for hazard assessment for sites situated on land	16
	re 8 — Flow diagram for hazard assessment on offshore drilling forms	17
	re 9 — Field strength versus distance from the transmitter d path)	33
	re 10 — Field strength versus distance from the transmitter path)	34
Figu wire	re 11 — Commercial EED showing winding and overwrapping of leading	ng 35
	are 12a) — Safe field strengths for Type I EED (includes the leading wind stances)	re 37

© BSI 30 June 2003 i