

Balance quality requirements of rigid rotors —

**Part 1: Method for determination of
permissible residual unbalance —**

**[ISO title: Mechanical vibration —
Balance quality requirements of rigid
rotors — Part 1: Determination of
permissible residual unbalance]**

UDC 62-253:62-755

Committees responsible for this British Standard

The preparation of this British Standard was entrusted by the General Mechanical Engineering Standards Committee (GME/-) to Technical Committee GME/21 upon which the following bodies were represented:

British Engine Group of SMMT
 British Maritime Technology
 British Steel Corporation
 Department of Trade and Industry (National Engineering Laboratory)
 Electricity Supply Industry in England and Wales
 Institute of Sound and Vibration Research
 Institution of Electronic and Radio Engineers
 Institution of Mechanical Engineers
 Lloyds Register of Shipping
 Ministry of Defence
 Motor Industry Research Association
 Power Generation Association (BEAMA Ltd.)
 Society of British Aerospace Companies Limited
 Society of Environmental Engineers
 United Kingdom Atomic Energy Authority

The following bodies were also represented in the drafting of the standard, through subcommittees and panels:

Engineering Equipment and Materials Users Association
 Coopted member

This British Standard, having been prepared under the direction of the General Mechanical Engineering Standards Committee, was published under the authority of the Board of BSI and comes into effect on 30 June 1987

© BSI 12-1998

The following BSI references relate to the work on this standard Committee reference GME/21 Draft (ref. 86/77850) announced in *BSI News* February 1987

Amendments issued since publication

Amd. No.	Date of issue	Comments
6365	June 1991	Indicated by a sideline in the margin

Contents

	Page
Committees responsible	Inside front cover
National foreword	ii
<hr/>	
0 Introduction	1
1 Scope and field of application	1
2 References	1
3 Pertinent aspects of the balancing problem	1
4 Permissible unbalance related to rotor mass	2
5 Quality grades relating service speed and permissible residual specific unbalance	4
6 Determination of balance quality requirements	4
7 Allocation of permissible residual unbalance to each correction plane on the basis of U_{per}	5
8 Determination of the residual unbalances	11
9 Sources of errors in balancing	12
<hr/>	
Annex Example for the general method described in 7.3.3.1 for two-plane balancing	15
<hr/>	
Figure 1 — Different representations of the same state of unbalance of a rigid rotor	3
Figure 2 — Maximum permissible residual specific unbalance value corresponding to various balance quality grades	7
Figure 3 — Rotor dimensions to be used for simplified method	8
Figure 4 — Rotor with overhung discs at both ends	9
Figure 5 — Rotors with couple correction planes I and II at a distance b less than one-third of the bearing span l	10
Figure 6 — Rotor dimensions to be used for general method calculations	10
Figure 7 — Determination of the response of the permissible residual unbalance to a trial mass	12
Figure 8 — Test procedure for determining the residual unbalance in one plane	13
Figure 9 — Error sources in end-drive elements	14
Figure 10 — Rotor dimensions	15
<hr/>	
Table 1 — Balance quality grades for various groups of representative rigid rotors	6
Table 2 — Typical examples of recommended deviations	12
<hr/>	
Publications referred to	Inside back cover
<hr/>	