

# Fracture mechanics toughness tests —

**Part 3: Method for determination of  
fracture toughness of metallic materials  
at rates of increase in stress intensity  
factor greater than  $3.0 \text{ MPa} \cdot \text{m}^{0.5} \text{ s}^{-1}$**

ICS 77.040.10

## Committees responsible for this British Standard

This British Standard was entrusted by Technical Committee ISE/NFE/4, Mechanical testing of materials, to Subcommittee ISE/NFE/4/4, Toughness testing, upon which the following bodies were represented:

British Non-Ferrous Metals Federation  
 GAMBICA Limited  
 HSE — Health and Safety Executive  
 Lloyd's Register  
 National Physical Laboratory  
 Network Rail  
 QinetiQ  
 Society of British Aerospace Companies Ltd.  
 UK Steel Association  
 United Kingdom Accreditation Service  
 Welding Institute

This British Standard was published under the authority of the Standards Policy and Strategy Committee on 23 March 2005

© BSI 2007

First published March 2005

### Amendments issued since publication

Amd. No.	Date	Comments
17334 Corrigendum No. 1	31 August 2007	In Foreword, added supersession detail.

The following BSI references relate to the work on this British Standard:

Committee reference  
 ISE/NFE/4/4  
 Draft for comment 03/303157 DC

ISBN 978 0 580 59480 9

# Contents

	Page
Committees responsible	Inside front cover
Foreword	iii
<hr/>	
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and designations	3
5 Principle	5
6 Test specimens	7
7 Specimen preparation and fatigue precracking	15
8 Test equipment	17
9 Test procedure	21
10 Analysis of test data	24
11 Check lists for qualification of data	38
12 Test report	38
<hr/>	
Figure 1 — Flow chart for the choice of fracture toughness parameter, specimen design and displacement measurement	6
Figure 2 — Proportional dimensions and tolerances for the rectangular section bend specimen	7
Figure 3 — Proportional dimensions and tolerances for the square section bend specimen	8
Figure 4 — Proportional dimensions and tolerances for the straight notch compact specimen	9
Figure 5 — Proportional dimensions and tolerances for the stepped notch compact specimen	10
Figure 6 — Acceptable fatigue crack starter notches and fatigue crack configurations	12
Figure 7 — Chevron notch	12
Figure 8 — Outward pointing knife edges and corresponding notch geometrics	13
Figure 9 — Outward pointing knife edges and corresponding notch geometrics	14
Figure 10 — Fixture for three point bend tests	19
Figure 11 — Typical design of clevis for applying a tensile force to a compact specimen using a circular hole in the clevis and a pin having a diameter of $(0.24 \pm_{0.015}^{0.005}) W$	20
Figure 12 — Typical design of clevis for applying a tensile force to a compact specimen using a hole with a flat in the clevis, and a pin having a diameter of $(0.24 \pm_{0.005}^{0.000}) W$	21
Figure 13 — Characteristic types of force versus displacement records in fracture tests	23
Figure 14 — Assessment of pop-in behaviour	25
Figure 15 — Principal types of force versus crack mouth opening gauge displacement records showing the limits of allowable force and displacement variation for $K_{Ic}$ determination	27
Figure 16 — Force variation limits for fracture toughness determination	28
Figure 17 — Limits of crack mouth opening gauge displacement variations for plane strain fracture toughness determination	29
Figure 18 — Definition of $V_p$ (for determination of CTOD)	30
Figure 19 — Limits of force and displacement for CTOD and J determination	31
Figure 20 — Force and load point displacement variation for fracture toughness determination	33