

**BS 8081:2015+A2:2018**  
Incorporating Corrigenda Nos. 1 and 2



**BSI Standards Publication**

## **Code of practice for grouted anchors**

**Publishing and copyright information**

The BSI copyright notice displayed in this document indicates when the document was last issued.

© The British Standards Institution 2018

Published by BSI Standards Limited 2018

ISBN 978 0 539 06019 5

ICS 91.200, 93.020

The following BSI references relate to the work on this document:

Committee reference B/526

Drafts for comment 15/30302283 DC; 17/30359711 DC; 18/30375081 DC

**Amendments/corrigenda issued since publication**

Date	Text affected
30 September 2017	A1: see Foreword
30 November 2017	C1: 11.3 subclause heading corrected
30 September 2018	A2: see Foreword
30 December 2019	C2: 3.2 and Annex B symbols and equations corrected

# Contents

	<b>Page</b>
<b>Foreword</b>	<b>iii</b>
1 Scope	1
2 Normative references	2
3 Terms, definitions, symbols and abbreviations	3
<i>Figure 1 — Grouted anchors</i>	9
4 General rules	13
<i>Table 1 — Recommended design and construction duties</i>	14
5 Limit states	19
6 Design situations	20
7 Design considerations	20
<i>Figure 2 — Grouted anchors</i>	22
<i>Figure 3 — Flow chart for the development of strategy for the monitoring and maintenance of grouted anchors</i>	24
8 Ultimate limit state design	24
9 Serviceability limit state design	24
10 Structural design	24
11 Anchor design	25
<i>Table 2 — Minimum resistance factors recommended for the calculation of the size of individual fixed anchor lengths prior to testing</i>	27
12 Materials	30
<i>Figure 4 — Typical encapsulation centralizers</i>	33
<i>Figure 5 — Typical bar centralizer</i>	34
<i>Figure 6 — Typical crosssection of centralizer/spacer unit for multi-strand tendon in temporary unprotected systems</i>	35
13 Durability	36
<i>Figure 7 — Typical coupler details in tendon free length of bar tendon</i>	40
<i>Figure 8 — Typical double corrosion protection of tendon bond length of strand tendon using a single corrugated sheath and polyester resin</i>	42
<i>Figure 9 — Typical double corrosion protection of tendon bond length of strand tendon using a double corrugated sheath and cement grout</i>	43
<i>Figure 10 — Tendon bond length protection for a ribbed bar tendon</i>	44
<i>Figure 11 — Typical double corrosion protection of tendon bond length of smooth or ribbed bar tendon using a double corrugated duct</i>	45
<i>Figure 12 — Typical double corrosion protection of restressable anchor head incorporating a strand tendon</i>	46
14 Execution	48
15 Considerations related to testing	58
16 Maintenance	58
17 Reporting	60
<b>Annex A</b> (informative) <b>Indicative record sheets</b>	<b>62</b>
<i>Table A.1 — Typical drilling, grouting and tendon installation record sheet</i>	63
<i>Table A.2 — Typical stressing record sheet</i>	65
<i>Table A.3 — Typical stressing results and analysis record sheet</i>	67
<b>Annex B</b> (informative) <b>Determination of the size of grouted anchors</b>	<b>68</b>
<i>Figure B.1 — Main types of cement injection grouted anchors</i>	69
<i>Figure B.2 — Detail of tube à manchette for pressure grouting control</i>	70
<i>Table B.1 — Rock/grout bond values that have been employed in practice</i>	72