

INTERNATIONAL  
STANDARD

**ISO/IEC**  
**9314-5**

First edition  
1995-02-01

---

---

**Information technology — Fibre  
Distributed Data Interface (FDDI) —  
Part 5:  
Hybrid Ring Control (HRC)**

*Technologies de l'information — Interface de données distribuées sur  
fibre (FDDI) —*

*Partie 5: Commande hybride par anneau (HRC)*



Reference number  
ISO/IEC 9314-5:1995(E)

## Contents

Foreword .....	iv
1 Scope .....	1
2 Normative references .....	1
3 Definitions .....	2
4 Conventions and abbreviations .....	6
4.1 Conventions .....	6
4.2 Abbreviations .....	7
5 General description .....	8
5.1 Traffic types .....	9
5.2 Transmission facilities .....	9
5.3 Bandwidth management .....	11
5.4 Station structure .....	12
6 HRC services.....	16
6.1 PHY to H-MUX services .....	17
6.2 H-MUX to MAC services .....	18
6.3 H-MUX to P-MAC services .....	19
6.4 H-MUX to I-MAC services .....	21
6.5 H-MUX to SMT services .....	24
6.6 I-MAC to CS-MUX services .....	30
6.7 I-MAC to SMT services .....	32
7 Facilities .....	34
7.1 H-MUX symbol set .....	34
7.2 Cycle .....	34
7.3 HRC protocol parameters .....	38
7.4 Variables .....	39
7.5 Timers .....	42
7.6 Counters .....	43
7.7 Signals.....	43
7.8 Functions.....	44
8 Operation .....	44
8.1 Ring operation overview .....	44
8.2 Error recovery.....	50
8.3 Structure.....	53
8.4 Cycle acquisition .....	57
8.5 Cycle generation process .....	67
8.6 Cycle exchange process .....	84

© ISO/IEC 1995

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Organization for Standardization

Case postale 56 • CH-1211 Genève 20 • Switzerland

Printed in Switzerland

## Annexes

A — Examples of the circuit-switch service class .....	86
B — FDDI station considerations .....	94
C — Isochronous call control procedures .....	99
D — Isochronous channel security .....	104
E — Isochronous bandwidth management .....	106
F — Logical ranking of monitors .....	108

## Figures

Figure 1 — Structure of FDDI standards .....	3
Figure 2 — HRC cycle structure .....	8
Figure 3 — Hybrid mode traffic types .....	9
Figure 4 — Bandwidth management hierarchy .....	11
Figure 5 — Data flow through an FDDI-II monitor station .....	13
Figure 6 — Data flow through an FDDI-II non-monitor station .....	14
Figure 7 — Architectural block diagram of the H-MUX .....	14
Figure 8 — Architectural block diagram of the I-MAC .....	16
Figure 9 — H-MUX cycle structure at 100 Mbps .....	34
Figure 10 — H-MUX cycle header .....	35
Figure 11 — Example of wideband channel interleaving .....	37
Figure 12 — Example of wideband channel sorting .....	37
Figure 13 — H-MUX structure .....	54
Figure 14 — HRC receive state diagram .....	58
Figure 15 — WBC template filter state diagram .....	62
Figure 16 — HRC cycle control state diagram .....	68
Figure 17 — HRC cycle generate state diagram .....	76
Figure 18 — WBC template generation state diagram .....	83
Figure A.1 — Example of a byte interleave burst mode CS-MUX .....	87
Figure A.2 — Example of a bit interleave burst mode CS-MUX .....	88
Figure A.3 — Example of a bit interleave continuous mode CS-MUX .....	88
Figure A.4 — Example of 2048 kbps G.703/G.732 bridge and associated CS-MUX .....	90
Figure A.5 — Example FDDI-II to G.703/G.732 protocol layers .....	91
Figure B.1 — FDDI-II clock tolerance budget .....	96
Figure B.2 — Sinusoidal and triangular jitter waves .....	96
Figure B.3 — FDDI-II allowable input jitter vs. network maximum jitter .....	97
Figure C.1 — Isochronous channel reservation .....	100
Figure C.2 — Isochronous call establishment .....	101
Figure C.3 — Isochronous call released from destination station .....	102
Figure C.4 — Isochronous call released from originating station .....	102
Figure C.5 — Isochronous channel release .....	103